

SECTION 5. TETHER DATA

5.1 General

This handbook would not be complete without providing the user with specific data and other information relevant to the analysis of tether applications. To the authors' knowledge, the best summarization of this data is contained in J. A. Carroll's Guidebook for Analysis of Tether Applications, published in 1985 under contract to the Martin Marietta Corporation. It provides a concise review of those technical areas which are essential to tether analyses. For the uninitiated, it is the first exposure they should have to ensure that they understand the broad implications of any application they might consider. From here, they can explore the many references given in the Bibliography.

The Guidebook is reproduced here in full, except for its bibliography which would be redundant. J. A. Carroll's introductory remarks and credits are presented below:

This Guidebook is intended as a tool to facilitate initial analyses of proposed tether applications in space. The guiding philosophy is that at the beginning of a study effort, a brief analysis of all the common problem areas is far more useful than a detailed study in any one area. Such analyses can minimize the waste of resources on elegant but fatally flawed concepts, and can identify the areas where more effort is needed on concepts which do survive the initial analyses.

In areas in which hard decisions have had to be made, the Guidebook is:

Broad, rather than deep
Simple, rather than precise
Brief, rather than comprehensive
Illustrative, rather than definitive

Hence the simplified formulas, approximations, and analytical tools included in the Guidebook should be used only for preliminary analyses. For detailed analyses, the references with each topic and in the bibliography may be useful. Note that topics which are important in general but not particularly relevant to tethered system analysis (e.g., radiation dosages) are not covered.

This Guidebook was presented by the author under subcontract RH4394049 with the Martin Marietta Corporation, as part of their contract NAS8-35499 (Phase II Study of Selected Tether Applications in Space) with the NASA Marshall Space Flight Center. Some of the material was adapted from references listed with the various topics, and this assisted the preparation greatly. Much of the other material evolved or was clarified in discussions with one or more of the following: Dave Arnold, James Arnold, Ivan Bekey, Guiseppe Colombo, Milt Contella, Dave Criswell, Don Crouch, Andrew Cutler, Mark Henley, Don Kessler, Harris Mayer, Jim McCoy, Bill Nobles, Tom O'Neil, Paul Penzo, Jack Slowey, Georg von Tiesenhausen, and Bill Thompson. The author is of course responsible for all errors, and would appreciate being notified of any that are found.

5.2 Generic Issues

MAJOR CONSTRAINTS IN MOMENTUM-TRANSFER APPLICATIONS

CONSTRAINT: APPLICATION;	ORBIT BASICS	TETHER DYNAMICS	TETHER PROPERTIES	TETHER OPERATIONS
All types	Apside location	Forces on end masses	μ meteoroid sensitivity	Tether recoil at release
Librating	Orbit planes must match	Tether can go slack		Facility attitude & "g"s variable
Spinning		High loads on payload		Retrieval can be difficult
Winching		High loads on payload		Extremely high power needed
Rendezvous				Short launch & capture windows
Multi-stage				Waiting time between stages
High deltaV	Gravity losses	Control of dynamics	Tether mass & lifetime	Retrieval energy; Facility a alt.

MAJOR CONSTRAINTS WITH PERMANENTLY-DEPLOYED TETHERS

CONSTRAINTS: APPLICATIONS;	ORBIT BASICS	TETHER DYNAMICS	TETHER PROPERTIES	TETHER OPERATIONS
All types	Aero. drag	Libration	Degradation, μ meteoroids & debris impact	Recoil & orbit changes after tether break
Electrodynamic	Misc changes in orbit	Plasma disturbances	High-voltage insulation	Consequences of failure <0.1 gee only, Docking awkward
Aerodynamic	Tether drag & heating			
Beanstalk (Earth)			Tether mass; debris impact	
Gravity Use: Hanging Spinning		Libration-Sensitive		

5.3 Orbit Equations and Data

5.3.1 Orbits and Orbital Perturbations

KEY POINTS Basic orbit nomenclature & equations are needed frequently in following pages. Comparison of tether & rocket operations requires orbit transfer equations.

The figures and equations at right are a summary of the aspects of orbital mechanics most relevant to tether applications analysis. For more complete and detailed treatments and many of the derivations, consult refs. 1-3.

The first equation in the box is known as the Vis Viva formulation, and to the right of it is the equation for the mean orbital angular rate, n . Much of the analysis of orbit transfer V s and tether behavior follows from those two simple equations. Some analyses require a close attention to specific angular momentum, h , so an expression for h (for compact objects) is also given here.

In general, six parameters are needed to completely specify an orbit. Various parameter sets can be used (e.g., 3 position coordinates & 3 velocity vectors). The six parameters listed at right are commonly used in orbital mechanics. Note that when $i=0$, becomes indeterminate (and unnecessary); similarly with when $e=0$. Also, i & are here referenced to the central body's equator, as is usually done for Low Earth Orbit (LEO). For high orbits, the ecliptic or other planes are often used. This simplifies calculation of 3rd body effects.

NOTES The effects of small V s on near-circular orbits are shown at right. The relative effects are shown to scale: a V along the velocity vector has a maximum periodic effect 4 times larger than that of the same, V perpendicular to it (plus a secular effect in which the others don't have). Effects of oblique or consecutive V s are simply the sum of the component effects. Note that out-of-plane V s at a point other than a node also affect .


For large V s, the calculations are more involved. The perigee and apogee velocities of the transfer orbit are first calculated from the Vis Viva formulation and the constancy of h . Then the optimum distribution of plane change between the two V s can be computed iteratively, and the required total V found. Typically about 90% of the plane change is done at GEO.

To find how much a given in-plane tether boost reduces the required rocket V , the full calculation should be done for both the unassisted and the tether-assisted rocket. This is necessary because the tether affects not only the perigee velocity, but also the gravity losses and the LEO/GEO plane change split. Each m/s of tether boost typically reduces the required rocket boost by 0.89 m/s (for hanging release) to 0.93 m/s (for widely librating release).

Note that for large plane changes, and large radius-ratio changes even without plane changes, 3-impulse "bi-elliptic" maneuvers may have the lowest total V . Such maneuvers involve a boost to near-escape, a small plane and/or perigee-adjusting V at apogee, and an apogee adjustment (by rocket or aerobrake) at the next perigee. In particular, this may be the best way to return aerobraking OTVs from GEO to LEO, if adequate time is available.


REFERENCES 1. A. E. Roy, Orbital Motion, Adam Hilger Ltd., Bristol, 1978.
2. Bate, Mueller, & White, Fundamentals of Astrodynamics, Dover Pub., 1971.
3. M. H. Kaplan, Modern Spacecraft Dynamics & Control, John Wiley & Sons, 1976.

Orbit & Orbit Transfer Equations






$v^2 = \mu \left(\frac{2}{r} - \frac{1}{a} \right)$	$n = \frac{2\pi}{T} = \sqrt{\mu/a^3}$
$v_{circ}^2 = \mu/r$	$h = \sqrt{\mu p} = r^2 \dot{\theta} = r v \cos \phi$
$v_{esc}^2 = 2\mu/r$	$\mu_{earth} = 398601 \text{ km}^3/\text{sec}^2$
	$\mu_x = G * \text{Mass of } x$



BASIC ORBIT EQUATIONS



ORBITAL ELEMENTS	
a	= semi-major axis
e	= eccentricity
i	= inclination
Ω	= long. of asc. node
ω	= argument of periaapsis
M_0	= position at epoch



Effects of Small ΔV s on Near-Circular Orbits



Total ΔV is minimized when $\frac{\sin y_{LEO}}{\sin y_{GEO}} = \frac{r_{LEO}}{r_{GEO}}$

Large Orbit Transfers (e.g., LEO—GEO)

5.3.2 Orbital Perturbations

KEY POINTS Differential nodal regression severely limits coplanar rendezvous windows. Apsidal recession affects STS deboost requirements from elliptical orbits. Third bodies can change the orbit plane of high-orbit facilities.

The geoid (earth's shape) is roughly that of a hydrostatic-equilibrium oblate ellipsoid, with a 296:297 polar:equatorial radius ratio. There are departures from this shape, but they are much smaller than the 1:297 oblateness effect and have noticeable effects only on geosynchronous and other resonant orbits.

The focus here is on oblateness, because it is quite large and because it has large secular effects on $\dot{\Omega}$ and $\dot{\omega}$ for nearly all orbits. (Oblateness also affects n , but this can usually be ignored in preliminary analyses.) As shown at right, satellites orbiting an oblate body are attracted not only to its center but also towards its equator. This force component imposes a torque on all orbits that cross the equator at an angle, and causes the direction of the orbital angular momentum vector to regress as shown.

$\dot{\Omega}$ is largest when i is small, but the plane change associated with a given $\dot{\Omega}$ varies with $\sin(i)$. Hence the actual plane change rate varies with $\sin(i)\cos(i)$, or $\sin(2i)$, and is highest near 45° . For near-coplanar rendezvous in LEO, the required out-of-plane ΔV changes by $78\sin(2i)$ m/s for each phasing "lap". This is independent of the altitude difference (to first order), since phasing & differential nodal regression rates both scale with a . Hence even at best a rendezvous may require an out-of-plane ΔV of 39 m/s. At other times, out-of-plane ΔV s of $2\sin(i)\sin(\Delta\theta/2)V_{\text{circ}}$ (= up to $2 V_{\text{circ}}$!) are needed.

NOTES The linkage between phasing and nodal regression rates is beneficial in some cases: if an object is boosted slightly and then allowed to decay until it passes below the boosting object, the total ΔV is nearly identical for both. Hence recapture need not involve any significant plane change.


Apsidal recession generally has a much less dominant effect on operations, since apsidal adjustments (particularly of low-e orbits) involve much lower ΔV s than nodal adjustments. However, tether payload boosts may often be done from elliptical STS orbits, and perigee drift may be an issue. For example, OMS deboost requirements from an elliptical STS orbit are tonnes lower (and payload capability much higher) if perigee is near the landing site latitude at the end of the mission. Perigee motion relative to day/night variations is also important for detailed drag calculations, and for electrodynamic day-night energy storage (where it smears out and limits the eccentricity-pumping effect of a sustained day-night motor-generator cycle).

Just as torques occur when the central body is non-spherical, there are also torques when the satellite is non-spherical. These affect the satellite's spin axis and cause it to precess around the orbital plane at a rate that depends on the satellite's mass distribution and spin rate.

In high orbits, central-body perturbations become less important and 3rd-body effects more important. In GEO, the main perturbations (~ 47 m/s/yr) are caused by the moon and sun. The figure at right shows how to estimate these effects, using the 3rd body orbital plane as the reference plane.

REFERENCES 1. A. E. Roy, Orbital Motion, Adam Hilger Ltd., Bristol, 1978.
2. Bate, Mueller, & White, Fundamentals of Astrodynamics, Dover Pub., 1971.

Orbital Perturbations



OBLATENESS CAUSES LARGE
SECULAR CHANGES IN $\dot{\Omega}$ & $\dot{\omega}$:


$\dot{\Omega}$: up to 1 rad/week in LEO

$\dot{\omega}$: up to 2 rad/week in LEO

Nodal Regression in LEO:


$$\dot{\Omega} \approx \frac{-63.6 \cos i \text{ rad/yr}}{(a/r_e)^{3.5} (1-e^2)^2}$$

$(r_e = 6378 \text{ km})$




For sun-synchronous orbits: $(i = 100^\circ \pm 1^\circ)$

$$\cos i \approx -.0988(a/r_e)^{3.5}(1-e^2)^2$$




For coplanar low- ΔV rendezvous
between 2 objects ($e_1 = e_2 \approx 0$, $i_1 = i_2$),
nodal coincidence intervals are:

$$\Delta t_{nc} \approx \frac{180 (\bar{a}/r_e)^{4.5}}{\Delta a |\cos i|} \text{ km} \cdot \text{yrs}$$




Apsidal recession in LEO:

$$\dot{\omega} \approx \frac{63.6(2 - 2.5 \sin^2 i)}{(a/r_e)^{3.5} (1-e^2)^2} \text{ rad/yr}$$



Motion of the longitude of
perigee with respect to the
sun's direction ("noon") is:

$$\dot{\omega}_s = \dot{\omega} + \dot{\Omega} - 2\pi/\text{yr}$$



Third-Body Perturbations (non-resonant orbits)

5.3.3 Aerodynamic Drag

KEY POINTS Tether drag affects tether shape & orbital life; atomic oxygen degrades tethers. Out-of-plane drag component can induce out-of-plane tether libration. The main value of payload boosting by tether is the increased orbital life. Unboosted orbital life of space facilities is affected by tether operations.

The figure at right shows the orbiter trolling a satellite in the atmosphere, as is planned for the 2nd TSS mission in the late 1980s. The tether drag greatly exceeds that on the end-masses and should be estimated accurately. The drag includes a small out-of-plane component that can cause ϕ -libration.

Tether drag is experienced over a range of altitudes, over which most of the terms in the drag equation vary: the air density ρ , the airspeed V_{rel} , and the tether width & angle of attack. In free-molecular flow, C_L is small, and C_D (if based on A) is nearly constant at 2.2. (C_D rises near grazing incidence, but then A is low.)

Only ρ varies rapidly, but it varies in a way which lends itself to simple approximations. Empirical formulae have been developed by the author and are shown at right. They give values that are usually within 25% of ref. 1, which is still regarded as representative for air density as a function of altitude & exosphere temperature. These estimates hold only for $\rho > 1E-14$, beyond which helium & hydrogen dominate & the density scale height H increases rapidly.

NOTES Note that over much of LEO, atomic oxygen is the dominant species. Hyperthermal impact of atomic oxygen on exposed surfaces can cause rapid degradation, and is a problem in low-altitude applications of organic-polymer tethers.

The space age began in 1957 at a 200-yr high in sunspot count. A new estimate of mean solar cycle temperatures (at right, from ref. 2), is much lower than earlier estimates. Mission planning requires both high & mean estimates for proper analysis. Ref. 2 & papers in the same volume discuss models now in use.


If the tether length L is $\ll H$, the total tethered system drag can be estimated from the total A & the midpoint V & θ . If $L \gg H$, the top end can be neglected, the bottom calculated normally, and the tether drag estimated from $1.1 \rho_{bottom} * \text{tether diameter} * H * V_{rel}^2$, with H & V_{rel} evaluated one H above the bottom of the tether. For L between these cases, the drag is bounded by these cases.

As shown at right, the orbital life of more compact objects (such as might be boosted or deboosted by tether) can be estimated analytically if T_{ex} is known. For circular orbits with the same r , V_{rel} & θ both vary with i , but these variations tend to compensate & can both be ignored in first-cut calculations.

The conversion of elliptical to "equal-life" circular orbits is an empirical fit to an unpublished parametric study done by the author. It applies when apsidal motions relative to the equator and relative to the diurnal bulge are large over the orbital life; this usually holds in both low & high- i orbits. For a detailed study of atmospheric drag effects, ref. 3 is still useful.


REFERENCES 1. U.S. Standard Atmosphere Supplements, 1966. ESSA/NASA/USAF, 1966.
2. K. S. W Champion, "Properties of the Mesosphere and Thermosphere and Comparison with CIRA 72", in The Terrestrial Upper Atmosphere, Champion and Roemer, ed.; Vol 3, #1 of Advances in Space Research, Pergamon, 1983.
3. D. G. King-Hele, Theory of Satellite Orbits in an Atmosphere, Butterworths, London, 1964.

Aerodynamic Drag




$$F_{drag} = .5 \int \rho C_D V_{rel}^2 \text{ Width } \delta r$$

$$V_e = .465 \cos(\text{Lat}) \text{ km/sec}$$




Lift & Drag in Free-Molecular Flow

$$(\bar{\lambda} \gg D_{tether}; \bar{\lambda} = \frac{10^{-7} \text{ kg/m}^3}{\rho})$$



Air Density as Function of Altitude & Exosphere Temperature

70 < Alt < 118:	$\rho \approx 11 \exp(-\text{Alt}/6)$	$-\rho/\dot{\rho} = H = 6 \text{ (km)}$
118 < Alt < 200:	$\rho \approx (\text{Alt}-95)^{-3}/2600$	$H = (\text{Alt}-95)/3$
200 < Alt $\rho > 1E-14$ &:	$\rho \approx \frac{1.47E-16 \text{ Tex}(3000-\text{Tex})}{(1+2.9(\text{Alt}-200)/\text{Tex})^{10}}$	$H = .1(\text{Alt}-200) + \text{Tex}/29$



$$\text{Circular Orbit Life} \approx \frac{.15 \text{ m}^2 \text{ yr}}{\text{kg}} \frac{M}{C_D A} \frac{(1 + 2.9(r-6578)/\text{Tex})^{11}}{3000 - \text{Tex}}$$

(-14 < Log ρ < -10)

$$\text{Equal-Life Circ. Alt.} \approx \text{Perigee} + \frac{\text{Apo} - \text{Per}}{2 + .154(\text{Apo}-\text{Per})/H_{\text{Per}}}$$

5.3.4 Thermal Balance

KEY POINTS Aerothermal heating of tethers is severe at low altitudes (<120 km). Tether temperature affects strength, toughness, & electrical conductivity. Extreme thermal cycling may degrade pultruded composite tethers. "View factors" are also used in refined micrometeoroid risk calculations.

Preliminary heat transfer calculations in space are often far simpler than typical heat transfer calculations on the ground, since the complications introduced by convection are absent. However the absence of the "clamping" effect of large convective couplings to air or liquids allows very high or low temperatures to be reached, and makes thermal design important.

At altitudes below about 140 km in LEO, aerodynamic heating is the dominant heat input on surfaces facing the ram direction. The heating scales with \sqrt{Q} as long as the mean free path λ is much larger than the object's radius. It is about equal to the energy dissipated in stopping incident air molecules. In denser air, shock & boundary layers develop. They shield the surface from the incident flow and make \sqrt{Q} rise slower as λ increases further. (See ref 1.)

Because tethers are narrow, they can be in free molecular flow even at 100 km, and may experience more severe heating than the (larger) lower end masses do. Under intense heating high temperature gradients may occur across non-metallic tethers. These gradients may cause either overstress or stress relief on the hot side, depending on the sign of the axial thermal expansion coefficient.

NOTES At higher altitudes the environment is much more benign, but bare metal (low-emittance) tethers can still reach high temperatures when resistively heated or in the sun, since they radiate heat poorly. Silica, alumina, or organic coatings >1 μm thick can increase emittance and hence reduce temperatures. The temperature of electrodynamic tethers is important since their resistance losses (which may be the major system losses) scale roughly with T_{abs} .

For a good discussion of solar, albedo, and long wave radiation, see ref. 2. The solid geometry which determines the gains from these sources is simple but subtle, and should be done carefully. Averaged around a tether, earth view-factors change only slowly with altitude & attitude, and are near 0.3 in LEO.

Surface property changes can be an issue in long-term applications, due to the effects of atomic oxygen, UV & high-energy radiation, vacuum, deposition of condensable volatiles from nearby surfaces, thermal cycling, etc. Hyperthermal atomic oxygen has received attention only recently, and is now being studied in film, fiber, and coating degradation experiments on the STS & LDEF.



Continued thermal cycling over a wide range (such as shown at bottom right) may degrade composite tethers by introducing a maze of micro-cracks. Also, temperature can affect the strength, stiffness, shape memory, and toughness of tether materials, and hence may affect tether operations and reliability.

-
- REFERENCES**
1. R. N. Cox & L.F. Crabtree, Elements of Hypersonic Aerodynamics, The English Universities Press Ltd, London, 1965. See esp. Ch 9, "Low Density Effects"
 2. F. S. Johnson, ed., Satellite Environment Handbook, Second Edition, Stanford University Press, 1965. See chapters on solar & earth thermal radiation.
 3. H. C. Hottel, "Radiant Heat Transmission," Chapter 4 of W.H. McAdams, HEAT TRANSMISSION, 3rd edition, McGraw-Hill, New York, 1954, pp. 55-125.

Thermal Balance


$$\begin{aligned} \dot{Q}_{\text{solar}} &= 1368 (\pm 40) \alpha_s A_{\perp} \text{ W/m}^2 \text{ (if in sun)} \\ &\quad \alpha_s \approx .1 - .9 \text{ (Kevlar} \approx .4) \\ \dot{Q}_{\text{emitted}} &= A \epsilon \sigma T^4 \quad (\sigma = 5.68 \text{E-}8 \text{ W/m}^2 \text{K}) \\ \dot{Q}_{\text{internal}} &= \text{ohmic} + \text{any others} \\ \dot{Q}_{\text{aerodyn.}} &= .5 \rho A_{\perp} V_{\text{rel}}^3 \text{ (see "Aero. Drag")} \\ \dot{Q}_{\text{albedo}} &= .37 (\pm .3) * 1368 (\pm 40) \text{ W/m}^2 \\ &\quad * \alpha_s A F \cos(\text{SunZenithAngle}) \text{ (if } > 0) \\ \dot{Q}_{\text{earth}} &= 215 (\pm 100) A \epsilon F \text{ W/m}^2 \end{aligned}$$

$$\epsilon \approx \begin{cases} .02 - .2 & \text{(metals)} \\ .9 & \text{(most non-metals)} \end{cases}$$




$$\begin{aligned} F_{\parallel} &= F_{\rightarrow} \\ F_{\rightleftharpoons} &\approx (F_{\leftarrow} + F_{\rightarrow} + 2F_{\nearrow})/4 \\ F_{\parallel} &< F_{\nearrow} < F_{\rightleftharpoons} \end{aligned}$$

Earth Viewfactors for Tethers



Inclination	β Range
0°	0-23.5°
28.5°	0-52°
$>66.5^\circ$	0-90°

(β = Sun out-of-plane angle)



5.3.5 Micrometeoroids and Debris

KEY POINTS Micrometeoroids can sever thin tethers & damage tether protection/insulation. Orbiting debris can sever tethers of any diameter.

At the start of the space age, estimates of meteoroid fluxes varied widely. Earth was thought to have a dust cloud around it, due to misinterpretation of data such as microphone noise caused by thermal cycling in spacecraft. By the late 1960s most meteoroids near earth were recognized to be in heliocentric rather than geocentric orbit. The time-averaged flux is mostly sporadic, but meteor showers can be dominant during their occurrence.

There is a small difference between LEO and deep-space fluxes, due to the focusing effect of the earth's gravity (which increases the velocity & flux), and the partial shielding provided by the earth & "sensible" atmosphere. For a typical meteoroid velocity of 20 km/sec, these effects combine to make the risk vary as shown at right in LEO, GEO, and beyond. The picture of a metal plate after hypervelocity impact is adapted from ref. 3.


The estimated frequency of sporadic meteoroids over the range of interest for most tether applications is shown by the straight line plot at right, which is adapted from ref. 4 & based on ref. 1. (Ref 1 is still recommended for design purposes.) For masses $<10^{-6}$ gm (<0.15 mm diam. at an assumed density of 0.5), the frequency is lower than an extension of that line, since several effects clear very small objects from heliocentric orbits in geologically short times.

NOTES Over an increasing range of altitudes and particle sizes in LEO, the main impact hazard is due not to natural meteoroids but rather to man-made objects. The plots at right, adapted from refs 4 & 5, show the risks presented by the 5,000 or so objects tracked by NORAD radars (see ref. 6). A steep "tail" in the 1995 distribution is predicted since it is likely that several debris-generating impacts will have occurred in LEO before 1995. Such impacts are expected to involve a 4-40 cm object striking one of the few hundred largest objects and generating millions of small debris fragments.





Recent optical detection studies which have a size threshold of about 1 cm indicate a population of about 40,000 objects in LEO. This makes it likely that debris-generating collisions have already occurred. Studies of residue in small surface pits on the shuttle and other objects recovered from LEO indicate that they appear to be due to titanium, aluminum, and paint fragments (perhaps flaked off satellites by micrometeoroid hits). Recovery of the Long Duration Exposure Facility (LDEF) later this year should improve this database greatly, and will provide data for LEO exposure area-time products comparable to those in potential long-duration tether applications.

- REFERENCES**
1. Meteoroid Environment Model—1969 [Near Earth to Lunar Surface], NASA SP-8013, March 1969.
 2. Meteoroid Environment Model—1970 [Interplanetary and Planetary], NASA SP-8038, October 1970.
 3. Meteoroid Damage Assessment, NASA SP-8042, May 1970. Shows impact effects.
 4. D. J. Kessler, "Sources of Orbital Debris and the Projected Environment for Future Spacecraft", in J. of Spacecraft & Rockets, Vol 18 #4, Jul-Aug 1981.
 5. D. J. Kessler, Orbital Debris Environment for Space Station, JSC-20001, 1984.
 6. CLASSY Satellite Catalog Compilations. Issued monthly by NORAD/J5YS, Peterson Air Force Base, CO 80914.

Micrometeoroids & Debris



$$[\text{RelRisk} \approx (1 - \text{Fearth})(.57 + .43r_e/r)]$$



5.4 Tether Dynamics and Control

5.4.1 Gravity Gradient Effects

KEY POINTS "Microgee" environments are possible only in small regions (~5 m) of a LEO facility. Milligee-level gravity is easy to get & adequate for propellant settling, etc.

The figure at right shows the reason for gravity-gradient effects. The long tank-like object is kept aligned with the local vertical, so that the same end always faces the earth as it orbits around it. If one climbs from the bottom to the top, the force of gravity gradually decreases and the centrifugal force due to orbital motion increases. Those forces cancel out only at one altitude, which is (nearly but not exactly) the altitude of the vehicle's center of mass.

At other locations an object will experience a net force vertically away from the center of mass (or a net acceleration, if the object is allowed to fall). This net force is referred to as the "gravity-gradient force." (But note that 1/3 of the net force is actually due to a centrifugal force gradient!) Exact and approximate formulas for finding the force on an object are given at right.

The force occurs whether or not a tether is present, and whether or not it is desirable. Very-low-acceleration environments, which are needed for some types of materials processing and perhaps for assembling massive structures, are only available over a very limited vertical extent, as shown at right. Putting a vehicle into a slow retrograde spin can increase the "height" of this low-gee region, but that then limits the low-gee region's other in-plane dimension.



NOTES Since gravity gradients in low orbits around various bodies vary with μ/r^3 , the gradients are independent of the size of the body, and linearly dependent on its density. Hence the gradients are highest (.3-.4 milligee/km) around the inner planets and Earth's moon, and 60-80% lower around the outer planets. In higher orbits, the effect decreases rapidly (to 1.6 microgee/km in GEO).

The relative importance of surface tension and gravity determines how liquids behave in a tank, and is quantified with the Bond number, $B_o = \frac{r \rho g}{\sigma}$. If $B_o > 10$, liquids will settle, but higher values ($B_o = 50$) are proposed as a conservative design criterion. On the other hand, combining a small gravity gradient effect ($B_o < 10$) with minimal surface-tension fluid-management hardware may be more practical than either option by itself. Locating a propellant depot at the end of a power tower structure might provide an adequate gravity-gradient contribution. If higher gravity is desired, but without deploying the depot, another option is to deploy an "anchor" mass on a tether, as shown at right.

Many nominally "zero-gee" operations such as electrophoresis may actually be compatible with useful levels of gravity (i.e., useful for propellant settling, simplifying hygiene activities, keeping objects in place at work stations, etc.). This needs to be studied in detail to see what activities are truly compatible.

REFERENCES 1. D. Arnold, "General Equations of Motion," Appendix A of Investigation of Electrodynamics Stabilization and Control of Long Orbiting Tethers, Interim Report for Sep 1979—Feb 1981, Smithsonian Astrophysical Observatory., March 1981.
2. K. R Kroll, "Tethered Propellant Resupply Technique for Space Stations," IAF-84-442, presented at the 35th LAF Congress, Lausanne Switzerland, 1984.

Gravity Gradient Effects



Crystal Growth	→ ?	? ← Calcium Retention
Latex Reactors	→ ?	? ← Walking
Electrophoresis	→ ?	? ← "Desktop" work
LSS Assembly	→ ?	? ← Eating, Hygiene
	→ ?	? ← Fluid Settling
Microgravity 10^{-3} G Full Gravity		

Potential Overlap of Regions for Low-Gee & Gee-Dependent Operations

5.4.2 Dumbbell Libration in Circular Orbit

KEY POINTS Libration periods are independent of length, but increase at large amplitude. Out-of-plane libration can be driven by weak forces that have a $2n$ component. Tethers can go slack if $\theta_{\max} > 65^\circ$ or $\phi_{\max} > 60^\circ$.

The two figures at right show the forces on a dumbbell in circular orbit which has been displaced from the vertical, and show the net torque on the dumbbell, returning it towards the vertical. The main difference between the two cases is that the centrifugal force vectors are radial in the in-plane case, and parallel in the out-of-plane case. This causes the net force in the out-of-plane case to have a smaller axial component and a larger restoring component, and is why ϕ -libration has a higher frequency than θ -libration.

Four aspects of this libration behavior deserve notice. First, the restoring forces grow with the tether length, so libration frequencies are independent of the tether length. Thus tether systems tend to librate “solidly”, like a dumbbell, rather than with the tether trying to swing faster than the end-masses as can be seen in the chain of a child's swing. (This does not hold for very long tethers, since the gravity gradient itself varies.) For low orbits around any of the inner planets or the moon, libration periods are roughly an hour.

Second, tethered masses would be in free-fall except for the tether, so the sensed acceleration is always along the tether (as shown by the stick-figures). Third, the axial force can become negative, for $\theta > 60^\circ$ or near the ends of retrograde in-plane librations $> 65.9^\circ$. This may cause problems unless the tether is released, or retrieved at an adequate rate to prevent slackness.


NOTES And fourth, although ϕ -libration is not close to resonance with any significant driving force, θ -libration is in resonance with several, such as out-of-plane components of aerodynamic forces (in non-equatorial orbits that see different air density in northward and southward passes) or electrodynamic forces (if tether currents varying at the orbital frequency are used). The frequency droop at large amplitudes (shown at right) sets a finite limit to the effects of weak but persistent forces, but this limit is quite high in most cases.

The equations given at right are for an essentially one-dimensional structure, with one principal moment of inertia far smaller than the other two: $A \ll B < C$. If A is comparable to B & C , then the θ -restoring force shrinks with $(B-A)/C$, and the θ -libration frequency by $\sqrt{(B-A)/C}$. Another limitation is that a coupling between θ & ϕ behavior (see ref. 1) has been left out. This coupling is caused by the variation of end-mass altitudes twice in each θ -libration. This induces Coriolis accelerations that affect ϕ . This coupling is often unimportant, since $4n$ is far from resonance with $1.73n$.

Libration is referenced to the local vertical, and when a dumbbell is in an eccentric orbit, variations in the orbital rate cause librations which in turn exert periodic torques on an initially uniformly-rotating object. In highly eccentric orbits this can soon induce tumbling.²

REFERENCES 1. D. Arnold, "General Equations of Motion," Appendix A of Investigation of Electrodynamic Stabilization and Control of Long Orbiting Tethers, Interim Report for Sep 1979—Feb 1981, Smithsonian Astrophysical Observatory., March 1981.
2. P.A. Swan, "Dynamics & Control of Tethers in Elliptical Orbits," IAF-84-361, presented at the 35th IAF Congress, Lausanne, Switzerland, October 1984.

Dumbbell Libration in Circular Orbit




$$\ddot{\theta} \approx -3n^2 \sin\theta \cos\theta = -1.5n^2 \sin(2\theta)$$

$$\dot{\theta} \approx \pm \sqrt{3} n \sqrt{\sin^2 \theta_{\max} - \sin^2 \theta}$$

$$(\dot{\theta} \approx \pm \sqrt{3} n \sin \theta_{\max} \text{ when } \theta=0)$$

$$n_{\theta} \approx n \sqrt{3 \cos \theta_{\max}}$$





$$\ddot{\phi} \approx -4n^2 \sin\phi \cos\phi = -2n^2 \sin(2\phi)$$

$$\dot{\phi} \approx \pm 2n \sqrt{\sin^2 \phi_{\max} - \sin^2 \phi}$$

$$(\dot{\phi} \approx \pm 2n \sin \phi_{\max} \text{ when } \phi=0)$$

$$n_{\phi} \approx 2n \sqrt{\cos \phi_{\max}}$$



5.4.3 Tether Control Strategies

KEY POINTS Open-loop control is adequate for deployment; full retrieval requires feedback Tension laws can control libration plus tether oscillations. Many other options exist for libration, oscillation, & final retrieval control.

The table at right shows half a dozen distinct ways in which one or more aspects of tethered system behavior can be controlled. In general, anything which can affect system behavior (and possibly cause control problems) can be part of the solution, if it itself can be controlled without introducing other problems.

Thus, for example, stiff tethers have sometimes been considered undesirable, because the stiffness competes with the weak gravity-gradient forces near the end of retrieval. However, if the final section of tether is stiff AND nearly straight when stress-free (rather than pig-tail shaped), then "springy beam" control laws using a steerable boom tip might supplement or replace other laws near the end of retrieval. A movable boom has much the same effect as a stiff tether & steerable boom tip, since it allows the force vector to be adjusted.

NOTES The basic concepts behind tension-control laws are shown at right. Libration damping is done by paying out tether when the tension is greater than usual and retrieving it at other times. This absorbs energy from the libration. As shown on the previous page, in-plane libration causes large variations in tension (due to the Coriolis effect), so "yoyo" maneuvers can damp in-plane librations quickly. Such yoyo maneuvers can be superimposed on deployment and retrieval, to allow large length changes (>4:1) plus large in-plane libration damping (or initiation) in less than one orbit, as proposed by Swet.¹

Retrieval laws developed for the TSS require more time than Ref. 1, because they also include damping of out-of-plane libration built up during station keeping. Rupp developed the first TSS control law in 1975;² much of the work since then is reviewed in (3). Recent TSS control concepts combine tension and thrust control laws, with pure tension control serving as a backup in case of thruster failure.⁴ Axial thrusters raise tether tension when the tether is short, while others control yaw & damp out-of-plane libration to allow faster retrieval.


A novel concept which in essence eliminates the final low-tension phase of retrieval is to have the end mass climb up the tether.⁵ Since the tether itself remains deployed, its contribution to gravity-gradient forces and stabilization remains. The practicality of this will vary with the application.

- REFERENCES**
1. C. J. Swet, "Method for Deploying and Stabilizing Orbiting Structures", U.S. Patent #3,532,298, October 6, 1970.
 2. C. C. Rupp, A Tether Tension Control Law for Tether Subsatellites Deployed Along Local Vertical, NASA TM X-64963, MSFC, September 1, 1975.
 3. V. J. Modi, Geng Chang-Fu, A.R. Misra, and Da Ming Xu, "On the Control of the Space Shuttle Based Tethered Systems," *Acta Astronautica*, Vol. 9, No. 6-7, pp. 437-443, 1982.
 4. A. K. Banerjee and T.R. Kane, "Tethered Satellite Retrieval with Thruster Augmented Control," AIAA 82-1-21, presented at the AIAA/AAS Astrodynamics Conference, San Diego, Calif., 1982.
 5. T. R. Kane, "A New Method for the Retrieval of the Shuttle-Based Tethered Satellite," *J. of the Astronaut. Sci.*, Vol 32, No. 3, July-Sept. 1984.

Tether Control Strategies

EFFECTIVENESS OF VARIOUS CONTROL CONCEPTS

APPLICATION CONTROL OUTPUT	Libration		Tether Oscillations		Endmass Attitude Osc.	
	In-plane	Out-of-plane	Longitudinal	Transverse	Pitch & Roll	Yaw
Tension	Strong	Weak (Note: tension control is weak when tether is short)	Strong	Strong	Strong	None
El. Thrust	Only if $M1 \neq M2$		None	Only odd harmonics	None	None
Thruster	Strong, but costly if prolonged			None	Strong, but costly if prolonged	
Movable mass	Good w/short tether		Possible but awkward		None	None
Stiff tether, Movable boom	Strong if tether is very short; weak otherwise					
Aerodynamic	High drag—use only if low altitude needed for other reasons.					



TENSION CONTROL FOR LIBRATION DAMPING... AND DEPLOYMENT/RETRIEVAL

5.4.4 Momentum Transfer Without Release

KEY POINTS Tethers merely redistribute angular momentum; they do not create it. Changes in tether length, libration, and spin all redistribute momentum. Momentum transfer out-of-plane or in deep space is possible but awkward.

The two figures at right show two different tether deployment (and retrieval) techniques. In both cases, the initial deployment (which is not shown) is done with RCS burns or a long boom. In the case at left, the tether is paid out under tension slightly less than the equilibrium tension level for that tether length. The tether is slightly tilted away from the vertical during deployment, and librates slightly after deployment is complete.

In the other case, after the initial near-vertical separation (to about 2% of the full tether length), the two end masses are allowed to drift apart in near-free-fall, with very low but controlled tension on the tether. Just under one orbit later, the tether is almost all deployed and the range rate decreases to a minimum (due to orbital mechanics). RCS burns or tether braking are used to cushion the end of deployment and prevent end mass recoil. Then the tether system begins a large-amplitude prograde swing towards the vertical.

NOTES In both cases, the angular momentum transferred from one mass to the other is simply, as stated in the box, the integral over time of the radius times the horizontal component of tether tension. In one case, transfer occurs mainly during deployment; in the other, mainly during the libration after deployment. In each case, momentum transfer is greatest when the tether is vertical, since the horizontal component of tether tension changes sign then.

An intermediate strategy—deployment under moderate tension—has also been investigated. However, this technique results in very high deployment velocities and large rotating masses. It also requires powerful brakes and a more massive tether than required with the other two techniques.


As discussed under Tether Control Strategies, changing a tether's length in resonance with variations in tether tension allows pumping or damping of libration or even spin. Due to Coriolis forces, in-plane libration and spin cause far larger tension variations than out-of-plane libration or spin, so in-plane behavior is far easier to adjust than out-of-plane behavior. Neglecting any parasitic losses in tether hysteresis & the reel motor, the net energy needed to induce a given libration or spin is simply the system's spin kinetic energy relative to the local vertical, when the system passes through the vertical.

Two momentum transfer techniques which appear applicable for in-plane, out-of-plane, or deep-space use are shown at right. The winching operation can use lighter tethers than other tethered-momentum-transfer techniques, but requires a very powerful deployer motor. The tangential V simply prevents a collision.


The spin-up operation (proposed by Harris Mayer) is similar to the winching operation. It uses a larger tangential V , a tether with straight and tapered sections, and a small motor. Retrieval speeds up the spin by a factor of $1/L^2$. Surprisingly, the long tapered section of tether can be less than half as massive as the short straight section that remains deployed after spin-up.

REFERENCES 1. J. Tschirgi, "Tether-Deployed SSUS-A, Report on NASA Contract NAS8-32842, McDonnell Douglas, April 1984.




Momentum Transfer




Momentum Transfer During
Deployment & Retrieval



Momentum Transfer During Libration
(after low-tension deployment)



Deployment Followed by Winching
(in orbit or in deep space)



One Spin-Up Technique
For Use in Deep Space

5.4.5 Orbit Transfer by Release or Capture

KEY POINTS The achievable orbit change scales with the tether length (as long as $r \ll r$). Retrograde-libration releases are inefficient, but allow concentric orbits. Apogee & perigee boosts have different values in different applications. Tethered capture can be seen as a time-reversal of a tether release operation.

The figures to the right show the size of the orbit changes caused by various tether operations. When released from a vertical tether, the end masses are obviously one tether length apart in altitude. The altitude difference 1/2 orbit later, r , varies with the operation but is usually far larger. The linear relationship shown becomes inaccurate when r approaches r . Tethered plane changes are generally limited to a few degrees and are not covered here.

Tether release leaves the center-of-mass radius at each phase angle roughly unchanged: if the upper mass is heavier, then it will rise less than the lower mass falls, and vice-versa. Note that the libration amplitude, α_{\max} , is taken as positive during prograde libration and negative during retrograde libration. Hence retrograde libration results in $r < 7L$. In particular, the pre-release & post-release orbits will all be concentric if $\alpha_{\max} = -60^\circ$. But since methods of causing -60° librations usually involve $+60^\circ$ librations (which allow much larger boosts by the same tether), prograde releases may usually be preferable unless concentric orbits are needed or other constraints enter in.


NOTES The relative tether length, mass, peak tension, and energy absorbed by the deployer brake during deployment as a function of (prograde) libration angle are all shown in the plot at right. Libration has a large effect on brake energy. This may be important when retrieval of a long tether is required, after release of a payload or after tethered-capture of a free-flying payload.

The double boost-to-escape operation at right was proposed by A. Cutler. It is shown simply as an example that even though momentum transfer is strictly a "zero sum game", a tethered release operation can be a "WIN-win game" (a large win & a small one). The small win on the deboost-end of the tether is due to the reduced gravity losses 1/2 orbit after release, which more than compensate for the deboost itself. Another example is that deboosting the shuttle from a space station can reduce both STS-deboost & station-reboost requirements.


Rendezvous of a spacecraft with the end of a tether may appear ambitious, but with precise relative-navigation data from GPS (the Global Positioning System) it may not be difficult. The relative trajectories required are simply a time-reversal of relative trajectories that occur after tether release. Approach to a hanging-tether rendezvous is shown at right. Prompt capture is needed with this technique: if capture is not achieved within a few minutes, one should shift to normal free-fall techniques. Tethered capture has large benefits in safety (remoteness) and operations (no plume impingement; large fuel savings). The main hazard is collision, due to undetected navigation or tether failure.

- REFERENCES**
1. G. Colombo, "Orbital Transfer & Release of Tethered Payloads," SAO report on NASA Contract NAS8-33691, March 1983.
 2. W.D. Kelly, "Delivery and Disposal of a Space Shuttle External Tank to Low Earth Orbit," J. of the Astronaut. Sci., Vol. 32, No. 3, July-Sept 1984.
 3. J.A. Carroll, "Tether-Mediated Rendezvous," report to Martin Marietta on Task 3 of contract RH3-393855, March 1984.
 4. J.A. Carroll, "Tether Applications in Space Transportation, IAF 84-438, at the 35th IAF Congress, Oct 1984. To be published in ACTA ASTRONAUTICA.

Orbit Transfer by Tethered Release or Capture




Effects of Tether Deployment and Release




$$\Delta r_K \approx L * (7 + \sqrt{48} \sin \theta_{\max})$$


Effect of Libration on Boost
(release at middle of swing)




Effects of Libration
(for equal- Δa boosts)



If done right, a tether
boost/deboost operation
can reduce ΔV -to-escape
for both end masses!



Trajectory for Tethered Capture from Above
(in tether-centered LV-LH reference frame)



5.4.6 Energy and Angular Momentum Balance

KEY POINTS Tether operations cause higher-order repartitions of energy & angular momentum. First-order approximations that neglect these effects may cause large errors. Extremely long systems have strange properties such as positive orbital energy.

The question and answer at right are deceptively simple. The extent to which this is so, and the bizarre effects which occur in extreme cases, can be seen in the 3 graphs at right. At top, deploying & retrieving two masses on a very long massless tether changes not only the top & bottom orbital radii but also that of the CM. In addition, the free-fall location drops below the CM. Other key parameter changes under the same conditions are plotted underneath.

Note that when the tether length exceeds about 30% of the original orbital radius, the entire system lies below the original altitude. Also, at a radius ratio near 1.95:1, the maximum tether length compatible with a circular orbit is reached. At greater lengths (and the initial amount of angular momentum), no circular orbit is possible at any altitude.

Tether retrieval at the maximum-length point can cause the system to either rise or drop, depending on the system state at that time. If it continues to drop, there is a rapid rise in tether tension, and the total work done by the deployer quickly becomes positive. This energy input eventually becomes large enough (at 2.89:1) to even make the total system energy positive. The system is unstable beyond this point: any small disturbance will grow and can cause the tether system to escape from the body it was orbiting. (See ref. 2.)

NOTES

The case shown is rather extreme: except for orbits around small bodies such as asteroids, tethers either will be far shorter than the orbital radius, or will greatly outweigh the end masses. Either change greatly reduces the size of the effects shown. The effects on arbitrary structures can be calculated using the equations listed at right, which are based on a generalization of the concept of "moments" of the vertical mass distribution. Changes in tether length or mass distribution leave h unchanged, so other parameters (including r_{cm} , n , and E) must change. (For short tethers, the changes scale roughly with the square of the system's radius of gyration.) In many cases different conditions are most easily compared by first finding the orbital radius that the system would have if its length were reduced to 0, $r_{Lt} = 0$.

The mechanism that repartitions energy and angular momentum is that length changes cause temporary system displacements from the vertical. This causes both torques and net tangential forces on the system, which can be seen by calculating the exact net forces and couples for a non-vertical dumbbell. The same effect occurs on a periodic basis with librating dumbbells, causing the orbital trajectory to depart slightly from an elliptical shape.


Other topics which are beyond the scope of this guidebook but whose existence should be noted are: eccentricity changes due to deployment, orbit changes due to resonant spin/orbit coupling, and effects of 2- & 3-dimensional structures.

-
- REFERENCES**
1. G. Colombo, M. Grossi, D. Arnold, & M. Martinez-Sanchez, "Orbital Transfer and Release of Tethered Payloads," continuation of NAS8-33691, final report for the period Sep 1979—Feb 1983, Smithsonian Astrophysical Observatory, March 1983. (In particular, see the table on page 21.)
 2. D. Arnold, "Study of an Orbiting Tethered Dumbbell System Having Positive Orbital Energy," addendum to final report on NAS8-35497, SAO, Feb 1985.

Energy & Momentum Balance

Question: What are the sources of the dumbbell spin angular momentum and deployer brake energy?

Answer: Orbit changes which repartition h & E .



For arbitrary nearly-one-dimensional vertical structures in circular orbit, analysis can be based on 5 "moments":

$$I_N = \sum M_i r_i^N \quad (\text{for } N: -2..2)$$

Each of these has physical meaning:

$$F_{\text{grav}} = \mu / I_{-2}$$


$$E_{\text{pot}} = -\mu / I_{-1}$$

$$\text{Mass} = I_0$$

$$F_{\text{cen}} = n^2 / I_1$$

$$h_{\text{tot}} = n / I_2$$

$$E_{\text{kin}} = .5 n^2 / I_2$$



Some other useful equations include:




$$r_{\text{cm}} = I_1 / I_0$$

$$n^2 = \mu I_{-2} / I_1$$

$$E = \mu ((.5 I_{-2} * I_2 / I_1) - I_{-1})$$

$$r_{(L_t=0)} = I_{-2} (I_2)^2 / (I_1 * (I_0)^2)$$

VERY-LONG-TETHER EFFECTS:



5.5 Tether Material Consideration

5.5.1 Tether Strength and Mass

KEY POINTS Tether strength/weight ratio constrains performance in ambitious operations. Required tether mass is easily derivable from ΔV and payload mass.

Usable specific strength can be expressed in various ways. Three ways are shown at right. V_c , L_c , and L_{1g} are here defined in terms of a typical design stress (new/m²) rather than the (higher) ultimate stress. Including the safety factor here streamlines the subsequent performance calculations. Higher safety factors are needed with non-metals than with metals since non-metals are often more variable in their properties, brittle, abrasion-sensitive, and/or creep-sensitive. A safety factor of 4 (based on short-term fiber strength) is typical for Kevlar, but the most appropriate safety factor will vary with the application;

The "characteristic velocity," V_c , is the most useful parameter in tetherboost calculations, because the tether mass can be calculated directly from V/V_c , independently of the orbit, and nearly independently of the operation. The table at the bottom, which lists tether/rocket combinations that have the lowest lifecycle mass requirements, holds whenever $k_{Vc}=1$ km/sec & $I_{sp}=350$ sec.

The characteristic length L_c is useful in hanging-tether calculations. It varies with the orbital rate n . (The simple calculation given assumes $L \ll r$; if this is not true, l/r effects enter in, and calculations such as those used in refs 3-5 must be used.) The safe 1-gee length L_{1g} is mainly useful in terrestrial applications, but is included since specific strength is often quoted this way. (Note that V_c and L_c vary with $\sqrt{\text{strength}}$, and L_{1g} directly with strength).

NOTES

The specific modulus is of interest because it determines the speed of sound in the tether (C =the speed of longitudinal waves), the strain under design load ($L/L=\{V_c^2/C\}^2$), & the recoil speed after failure under design load ($= V_c^2/C$).


Tether mass calculations are best done by considering each end of the tether separately. If $M_{pl} \gg M_{p2}$, then M_{tl} can be neglected in preliminary calculations.

Du Pont's Kevlar is the highest-specific strength fiber commercially available. Current RND efforts on high-performance polymers indicate that polyester can exhibit nearly twice the strength of Kevlar.² Two fiber producers have already announced plans to produce polymers with twice the specific strength of Kevlar.

In the long run, the potential may be greater with inorganic fibers like SiC & graphite. Refs. 3-5 focus on the requirements of "space elevators." They discuss laboratory tests of single-crystal fibers and suggest that 10-fold improvements in specific strength (or 3-fold in V_c & L_c) are conceivable.



-
- REFERENCES**
1. "Characteristics and Uses of Kevlar 49 Aramid High Modulus Organic Fiber" available from Du Pont's Textile Fibers Department, 1978.
 2. G. Graff, "Superstrong Plastics Challenge Metals," High Technology magazine, February 1985, pp. 62-63.
 3. J. Isaacs, H. Bradner, G. Backus, and A. Vine, "Satellite Elongation into a True "Skyhook"; a letter to Science, Vol. 151, pp. 682-683, Feb 11, 1966.
 4. J. Pearson, "The Orbital Tower: a Spacecraft Launcher Using the Earth's Rotational Energy," Acta Astronautica, Vol.2, pp. 785-799, Pergamon, 1975.
 5. H. Moravec, "A Non-Synchronous Orbital Skyhook," J. of the Astronautical Sciences, Vol. YXV, No. 4, pp. 307-322, Oct-Dec 1977.

Specific Strength and Required Tether Mass




* Design stress is assumed to be 1/2 the ultimate strength for metals and 1/4 the short-term individual fiber strength for other materials.

SPECIFIC STRENGTH & MODULUS OF SEVERAL TETHER MATERIALS



* $k = \begin{cases} 1.00 & \text{for spinning operations} \\ 1.15 & \text{for hanging} \\ 1.21 \pm 0.01 & \text{for swinging} \\ 1.41 & \text{for winching} \end{cases}$

$\Delta V = \text{Sum of perigee + apogee boosts}$



Expected # of uses	1	10	100	1000
Best tether ΔV , km/s	.14	.9	1.8	2.6
Required M_t/M_p	.02	1	11	95

(For $kV_c = 1 \text{ km/s}$ and rocket $I_{sp} = 350$ seconds; marginal deployer & dry rocket masses neglected.)

Best Tether ΔV for Combined Tether/Rocket Boosts

5.5.2 Tether Impact Hazards

KEY POINTS Micrometeoroids can sever thin tethers & damage tether protection/insulation. Orbiting debris (or other tethers) can sever tethers of any diameter. Debris could impact an Earth-based "Space Elevator" over once per year.

Sporadic micrometeoroids are usually assumed to have an typical density of about .5 and a typical impact velocity in LEO of approximately 20 km/sec.¹ At impact speeds above the speed of sound, solids become compressible and the impact shock wave has effects like those of an explosion. For this reason, the risk curve assumes that if the EDGE of an adequately large meteoroid comes close enough to the center of the tether (within 45° or $.35 D_t$), failure will result.

Experiments done by Martin Marietta on TSS candidate materials have used glass projectiles fired at 6.5 km/sec, below the (axial) speed of sound in Kevlar. Two damaged tethers from those tests are shown at right. The scaling law used ($.5V^{0.67}$) indicates that this is representative of orbital conditions, but that law (used for impacts on sheet metal) may not apply to braided fibers.

For tethers much thicker than 10 mm or so (depending on altitude), the risk does not go down much as D_t increases, because even though the micrometeoroid risk still decreases, the debris risk (which INCREASES slightly with D_t) begins to dominate. As with micrometeoroids, the tether is assumed to fail if any part of the debris passes within $0.35 D_t$ of the center of the tether.

NOTES

The debris risk at a given altitude varies with the total debris width at that altitude. This was estimated from 1983 CLASSY radar cross-section (RCS) data, by simply assuming that $W = \text{Sqrt}(\text{RCS})$ and summing $\text{Sqrt}(\text{RCS})$ over all tracked objects in LEO.⁶ This underestimates W for objects with appendages, and over-estimates it for non-librating elongated objects without appendages.



CLASSY RCS data are expected to be accurate for $\text{RCS} > 7 \text{ m}^2$. The 700 objects with $\text{RCS} > 7 \text{ m}^2$ account for 3 km of the total 5 km width, so errors with smaller objects are not critical. Small untracked objects may not add greatly to the total risk: 40,000 objects averaging 2 cm wide would increase the risk to a 1-cm tether by only 20%. W was assumed independent of altitude, so the distribution of risk with altitude could be estimated by simply scaling Figure 1 from Ref. 4.

As shown at right, debris impact with a space elevator could be expected more than once per year at current debris populations. The relative density at 0° latitude was estimated from data on pp. 162-163 of ref. 6.

Similar calculations can be made for two tethers in different orbits at the same altitude. If at least one is spinning or widely-librating, the mutual risks can exceed 0.1 cut/km·yr. This makes "tether traffic control" essential.




-
- REFERENCES**
1. Meteoroid Environment Model—1969 [Near Earth to Lunar Surface], NASA SP-8013, March 1969.
 2. Meteoroid Environment Model—1970 [Interplanetary and Planetary], NASA SP-8038, October 1970.
 3. Meteoroid Damage Assessment, NASA SP-8042, May 1970. (Shows impact effects)
 4. D. J. Kessler, "Sources of Orbital Debris and the Projected Environment for Future Spacecraft", in J. of Spacecraft & Rockets, Vol 18 #4, Jul-Aug 1981.
 5. D. J. Kessler, Orbital Debris Environment for Space Station, JSC-20001, 1984.
 6. CLASSY Satellite Catalog Compilations as of 1 Jan 1983, NORAD/J5YS, 1983.

Impact Hazards for Tethers



For tethers with $D_t > 1 \text{ (mm)}$,
& Max non-fatal $D_m = .25 D_t$,

$$\frac{\mu\text{m cuts}}{\text{Km.Yr}} \approx D_t^{-2.6}$$



Debris Risk to the Lowest 4000 km
of an Earth-based Space Elevator:

$$\begin{aligned} \text{Risk} &= \frac{\Sigma \text{Width} \cdot \bar{V} \cdot \text{RelDensity at } \lambda=0}{\text{Earth "Surface Area" at Alt}} \\ &= \frac{\sim 5 \text{ km} \cdot \sim 7.3 \text{ km/sec} \cdot \sim .72}{4 \cdot \pi \cdot \text{Sqr}(\sim 7378 \text{ km})} \\ &\approx 3.9\text{E-}8/\text{sec} \approx \boxed{1.2 \text{ cuts/year}} \end{aligned}$$

5.6 Electrodynamic Tethers

5.6.1 Interactions with Earth's Magnetic Field and Plasma

KEY POINTS Tether (& other) resistance can limit the output of electrodynamic tethers. Electron collection methods & effectiveness are important—and uncertain.

Since the publication of ref. 1, 20 years ago, electrodynamic tether proposals and concepts have been a frequent source of controversy, mainly in these areas:

1. What plasma instabilities can be excited by the current?
2. What is the current capacity of the plasma return loop?
3. What is the best way to collect electrons from the plasma?

The first Tethered Satellite mission may do much to answer these questions. The discussion below and graphics at right merely seek to introduce them.

The current flowing through an electrodynamic tether is returned in the surrounding plasma. This involves electron emission, conduction along geomagnetic field lines down to the lower ionosphere, cross-field conduction by collision with neutral atoms, and return along other field lines.

The tether current causes a force on the tether (and on the field) perpendicular to both the field and the tether (horizontal, if the tether is vertical). Motion of the tether through the geomagnetic field causes an EMF in the tether. This allows the tether to act as a generator, motor, or self-powered ultra-low-frequency broadcast antenna.² The motion also causes each region of plasma to experience only a short pulse of current, much as in a commutated motor.







NOTES

Based on experience with charge neutralization of spacecraft in high orbit, it has been proposed that electrons be collected by emitting a neutral plasma from the end of the tether, to allow local cross-field conduction.³ In GEO, the geomagnetic field traps a plasma in the vicinity of the spacecraft, and "escape" along field lines may not affect its utility. This may also hold in high-inclination orbits in LEO. But in low inclinations in LEO, any emitted plasma might be promptly wiped away by the rapid motion across field lines.

A passive collector such as a balloon has high aerodynamic drag, but a end-on sail can have an order of magnitude less drag. The electron-collection sketch at bottom right is based on a preliminary analysis by W. Thompson.⁵ This analysis suggests that a current moderately higher than the electron thermal current ($=Ne \cdot \sim 200 \text{ km/sec}$) might be collected on a surface normal to the field. This is because collecting electrons requires that most ions be reflected away from the collection region as it moves forward. This pre-heats and densifies the plasma ahead of the collector. The voltage required for collection is just the voltage needed to repel most of the ions, about 12 V.

-
- REFERENCES**
1. S. D. Drell, H. M. Foley, & M. A. Ruderman, "Drag and Propulsion of Large Satellites in the Ionosphere: An Alfvén Propulsion Engine in Space," *J. Of Geophys. Res.*, Vol. 70, No. 13, pp. 3131-3145, July 1965.
 2. M. Grossi, "A ULF Dipole Antenna on a Spaceborne Platform of the PPEPL Class," Report on NASA Contract NAS8-28203, May 1973.
 3. R. D. Moore, "The Geomagnetic Thruster—A High Performance "Alfvén Wave" Propulsion System Utilizing Plasma Contacts," ALGA Paper No. 66-257.
 4. S. T. Wu, ed., University of Alabama at Huntsville/NASA Workshop on The Uses of a Tethered Satellite System, Summary Papers, Huntsville AL, 1978. See papers by M. Grossi et al, R. Williamson et al., and N. Stone.
 5. W. Thompson, "Electrodynamic Properties of a Conducting Tether," Final Report to Martin Marietta Corp. on Task 4 of Contract RH3-393855, Dec. 1983.

Electrodynamic Tether Principles



Top View of Electron Collection

5.6.2 Electrodynamic Orbit Changes

KEY POINTS Electrodynamic tether use will affect the orbit—whether desired or not. Station keeping and/or large orbit changes without propellant use are possible.

The offset dipole approximation shown at right is only a first approximation to the geomagnetic field: harmonic analyses of the field give higher-order coefficients up to 20% as large as the fundamental term. Ref. 1 contains computerized models suitable for use in detailed electrodynamic studies.

The geomagnetic field weakens rapidly as one moves into higher orbits, and becomes seriously distorted by solar wind pressure beyond GEO. However, ohmic losses in a tether are already significant in LEO, so electrodynamic tethers are mainly useful in low orbits where such distortions are not significant.

As the earth rotates, the geomagnetic field generated within it rotates also, and the geomagnetic radius and latitude of a point in inertial space vary over the day. If a maneuvering strategy which repeats itself each orbit is used (necessary unless the spacecraft has large diurnal power storage capacity), then the average effect, as shown at right, will be a due east thrust vector.

Variations in geomagnetic latitude (and thus in B_h) cancel out variations in the component of flight motion perpendicular to the field, so these variations do not cause large voltage variations in high-inclination orbits. (Note that the relevant motion is motion relative to a rotating earth.) Out-of-plane libration, variations in geomagnetic radius, and diurnal variation of the "geomagnetic inclination" of an orbit can all cause voltage variations. Peak EMFs (which drive hardware design) may approach 400 V/km.


NOTES However these variations need not affect the thrust much if a spacecraft has a variable-voltage power supply: neglecting variations in parasitic power, constant power investment in a circular orbit has to give constant in-plane thrust. The out-of-plane thrust is provided "free" (whether desired or not). Average voltage & thrust equations for vertical tethers are shown at right.

The table shows how to change all six orbital elements separately or together. Other strategies are also possible. Their effects can be calculated from the integrals listed. For orbits within 11° of polar or equatorial, diurnally-varying strategies become more desirable. Computing their effects requires using the varying geomagnetic inclination instead of i (& moving it inside the integral). Note that the "DC" orbit-boosting strategy also affects i . This can be canceled out by superimposing a $-2 \cos(2\)$ current on the DC current.


As discussed under Electrodynamic Libration Control Issues, eccentricity and apside changes can strongly stimulate ϕ -libration unless the spacecraft center of mass is near the center of the tether. Other maneuvers should not do this, but this should be checked using high-fidelity geomagnetic field models.

- REFERENCES**
1. E. G. Stassinopoulos & G. D. Mead, ALLMAG, GDALMG, LINMA:Computer Programs for Geomagnetic Field & Field-Line Calculations, Feb. 1972, NASA Goddard.
 2. R. D. Moore, "The Geomagnetic Thruster—A High Performance "Alfven Wave" Propulsion System Utilizing Plasma Contacts," AIAA Paper No. 66-257.
 3. H. Alfven, "Spacecraft Propulsion; New Methods," Science, Vol. 176, 14 Apr 1972, pp. 167-168.


Electrodynamic Orbit Changes



OFFSET DIPOLE APPROXIMATION TO GEOMAGNETIC FIELD



EFFECT OF EARTH'S SPIN ON TIME-AVERAGED FIELD




HOW TO CHANGE ORBITS USING AN ELECTRODYNAMIC TETHER

Element	Strategy	Thrust Vector	Effect
Semimajor axis	DC		$\Delta a \approx \cos(i) \frac{kl}{m} \int i \, dt$
Phase	Sawtooth		$\Delta \phi \approx \cos(i) \frac{1.5 kl n}{m a} \int i \, t \, dt$
Eccentricity	$\cos(\theta)$		$\Delta e \approx \cos(i) \frac{kl}{m a} \int i \cos(\theta) \, dt$
Line of apsides	$\sin(\theta)$		$\Delta \omega \approx \cos(i) \frac{kl}{m a e} \int i \sin(\theta) \, dt$
Inclination	$-\cos(2\phi)$		$\Delta i \approx \frac{-kl}{2 m a} \int i \sin(i) \cos^2(\phi) \, dt$
Ascending node	$-\sin(2\phi)$		$\Delta \Omega \approx \frac{-kl}{2 m a} \int i \sin(\phi) \cos(\phi) \, dt$

θ = POSITION OF VEHICLE WITH REFERENCE TO ITS PERIGEE

ϕ = POSITION WITH REFERENCE TO ASCENDING NODE

k = $\sim 4 \text{ TONNES PER AMPERE DAY} \times (r_e/r)^{4.5}$



l = TETHER LENGTH

m = TOTAL VEHICLE MASS

n = ORBITAL ANGULAR RATE

5.6.3 Tether Shape and Libration Control

KEY POINTS Properly controlled AC components can be used to control in-plane and out-of-plane libration. Solar-energy storage and eccentricity changes strongly stimulate out-of-plane libration. AC currents other than 1 & 3/orbit should not affect out-of-plane libration much.

The maneuvering strategies on the previous page have assumed that electrodynamic tethers will stay vertical. However, as shown at right, the distributed force on the tether causes bowing, and that bowing is what allows net momentum transfer to the attached masses. Note that net momentum can be transferred to the system even if the wire is bowed the wrong way (as when the current is suddenly reversed); momentum transferred to the wire gets to the masses later.

This figure also illustrates two other issues:

1. Bowing of the tether causes it to cross fewer field lines.
2. Unequal end masses and uniform forces cause overall torques & tilting.

The bowing causes the tether to provide less thrust while dissipating the same parasitic power. The net force on the system is the same as if the tether were straight but in a slightly weaker magnetic field.

The torque on the system causes it to tilt away from the vertical, until the torque is balanced by gravity-gradient restoring torques. For a given system mass and power input, disturbing torques vary with L and restoring torques with L^2 , so longer systems can tolerate higher power. The mass distribution also affects power-handling capability, as seen in the sequence at top right.

NOTES



Modulating the tether current modulates any electrodynamic torques. Current modulation at 1.73 n can be used to control in-plane libration. Out-of-plane torques can also be modulated, but another control logic is required. This is because the once-per-orbit variation in out-of-plane thrust direction makes a current with frequency F (in cycles per orbit) cause out-of-plane forces and torques with frequencies of $F-1$ and $F+1$, as shown in the Fourier analysis at bottom right. Hence out-of-plane libration control ($F=2$) requires properly phased $F=1$ or $F=3$ currents. Higher frequencies can damp odd harmonics of any tether bowing oscillations. Control of both in- & out-of-plane oscillations may be possible since they have the same frequencies and thus require different currents.

Applications that require significant $F=1$ components for other reasons can cause problems. Four such strategies are shown at right. Sin & Cos controls allow adjustment of eccentricity or inclination. The two "Sign of ..." laws allow constant power storage over 2/3 of each orbit and recovery the rest of the orbit. These laws would be useful for storing photovoltaic output for use during dark periods.

These strategies drive out-of-plane libration (unless the center of mass is at the center of the tether). The libration frequency decreases at large amplitudes, so if the system is not driven too strongly, it should settle into a finite-but-large-amplitude phase-locked loop. This may be unacceptable in some applications, due to resulting variations in gravity or tether EMF. In some cases, such as eccentricity changes, adding a $F=3$ component might cancel the undesired effect of an $F=1$ current while keeping the desired effect.


REFERENCE 1. G. Colombo, M. Grossi, M. Dobrowolny, and D. Arnold, Investigation of Electrodynamic Stabilization & Control of Long Orbiting Tethers, Interim Report on Contract NAS8-33691, March 1981, Smithsonian Astrophysical Observatory.

Electrodynamic Libration Control Issues



FOR CONTROL OF:	MODULATE I AT:
Out-of-plane libration*	1 n or 3 n
In-plane libration*	1.73 n
Tether oscillations	>5 n

* I or mass distribution must be lopsided



Tether Current:

$$I = 1.0$$

$$I = \sin \phi$$


$$I = \cos \phi$$

$$I = \text{Sign of } (.5 + \sin \phi)$$

$$I = \text{Sign of } (.5 + \cos \phi)$$

$$I = \sin 2\phi$$

$$I = \cos 2\phi$$



Fourier Analysis of Out-Of-Plane Forces:

	1n	2n	3n
$I = 1.0$.50	0	0
$I = \sin \phi$	0	.50*	0
$I = \cos \phi$	0	.50	0
$I = \text{Sign of } (.5 + \sin \phi)$.50	.65	.39
$I = \text{Sign of } (.5 + \cos \phi)$.03	.51	.07
$I = \sin 2\phi$.50	0	.50
$I = \cos 2\phi$.50	0	.50

* drives ϕ libration

SECTION 6.0 SPACE SCIENCE AND TETHERS

6.1 Overview

Some scientific applications of tethers have been presented already in other sections of this handbook (see section 3 and 4). In this section we will illustrate the role that tethers can play in the future advancement of space science. We hope that this section will grow in the next editions.

According to the Non-advocate Tether Systems Applications Review (1993), chaired by Dr. M. Greenfield (see “contacts” Section), “...Space tether technology has the near-term potential to meet a broad range of science and technological aspects. The unique capabilities of tether technology enable the acquisition of science otherwise not achievable and can provide concepts for space applications...”. Copies of report can be obtained either from the chairman or from the editors.

Space research with tethers has emphasized two particular applications: 1) Reaching otherwise inaccessible flight regions with downward deployed tethers; 2) Active experimentation with the surrounding plasma.

A good example of the effort carried on by the scientific community is the workshop held in Ann Harbor, Michigan in July 1994. Copies of the Executive Summary can be obtained by Prof. B. Gilchrist (see “contacts” Section). The focus of this workshop was on how Ionospheric-Thermospheric-Mesospheric (ITM) Science can benefit from spaceborne tethers. NASA’s sponsored TIMED mission promises to add substantially to the knowledge of the global response of the ITM region.

A multi-mass tether system could add many “in-situ” data on the effects of small scale spatial structures and its interactions (see “Applications” Section). As the reports quotes “... Just as the advancement of remote sensing technology enabled the TIMED mission to be conceived, the ability of tethered payloads in space with spatial separations ranging for 1 Km to 100 km will enable a program of in-situ multiprobe diagnostics of the ITM region to be undertaken.”. The workshop identified the following areas that would benefit from tethered spacecraft:

- Magnetospheric-Ionospheric coupling: Energy dissipation and configuration of three dimensional high latitude current systems.
- Effects of plasma structures on large and small scale electrodynamics.
- Ion-neutral momentum and energy exchange at different spatial scales.
- Momentum and energy transport processes by gravity waves.
- Thermospheric cooling (energy loss) through radiative emissions.
- The role of electromagnetic and electrostatic waves in energy transfer processes.
- The generation and flow of electrical currents in the ITM region

A task group chaired by prof. Heelis followed up the objectives laid out by the Michigan Workshop. The key science questions to be answered from a series of “in-situ” tether-aided observations in the lower thermosphere, highlighted significant advances as:

- Determination of the effective scales over which polarization electric fields are generated and how they map along the magnetic field lines.
- Determination of the wind effectiveness in producing polarization fields and driving field-aligned currents.
- Identification of the type winds responsible for conductivity variations and those responsible for electric field generation.
- Assessment of gravity wave generators and of possible seed mechanism for F-region plasma instabilities.
- Assessment of the relevance of thermospheric cooling to global change and improvement of prediction of the future physical characteristics in the thermosphere, mesosphere and stratosphere.
- Identification of the response of the lower ionosphere-thermosphere to large scale weather systems and transient phenomena associated with lightning.

The measurements that could address the above questions are listed in the following table.

<i>Parameter</i>	<i>Dynamic Range</i>	<i>Accuracy</i>	<i>Resolution</i>	<i>Sample Interval</i>
Neutral Atmospheric comp.	10^5 - 10^{11} cm ⁻³	<± 10% and smaller for major species	M/M =1 at M=30 5%	<4 Km
Neutral Wind Vector	-500 to 500 m/s	± 10%	1 m/s	<4 Km
Ion Composition	1 to 10^5 cm ⁻³	± 10%	M/M =1 at M=16 1%	<4 Km Comp. <500 m Total
Ion Drift Velocity vector	-2 to +2 Km/s	± 10%	1 m/s	<500 m
Ion/Electron/ Neutral Temp.	300 to 3000 K	± 10%	50 K	<4 Km
Electric field Vector d.c.	-200 to +200 mV/m	± 10%	0.05 mV/m	<4 Km
Current Density/ Magnetic field	-65 to +65 KnT	± 0.1%	0.01%	<1 Km
FUV Imaging	10 R to 50 KR	± 0.5%	N/A	<1 Km
Energetic Particles	10 eV to 30 KeV 10^7 to 10^{10} cm ⁻² s ⁻¹ sr ⁻¹ eV ⁻¹	± 5%	N/A	<4 Km 30 deg pitch angle
IR Emissions 13-17.5 μm	2×10^{-9} to 5×10^{-8} W cm ⁻² sr ⁻¹	10%	R/R 3%	120 Km
4.17-6.25 μm	2×10^{-8} to 2×10^{-7}	5%	R/R 0.4%	120 Km

More information on the instrumentation and the engineering aspects of this mission can be found in the section "Proposed Missions" (ATM Mission). A report entitled "Tether-based Investigation of the Ionosphere and Lower Thermosphere (TIILT)" has been prepared to present the scientific rationale behind this type of mission as well as the measurements and instrumentation. Copies of this report can be obtained by Prof. Heelis.

There are other missions, however, that would benefit from tethers. For example, ACTIVE spacecraft, launched by the former USSR in 1989, aimed at investigating VLF radiowave propagation and wave-particle interaction in the magnetosphere using a 10 KW VLF transmitter with a large loop antenna (20 m diameter). Electromagnetic effects occurring near the spacecraft were monitored by a coorbiting subsatellite, as shown in figure 6.1.




Figure 6.1 Active spacecraft and subsatellite

The primary objectives of the ACTIVE program were as follows:

- 1) Radiation Properties of the loop antenna.
- 2) Spatial structure of the electromagnetic fields in the near zone (≤ 10 km).
- 3) Nonlinear effects in the near zone
- 4) Propagation of waves in the whistler mode, and their reflection from the ionosphere
- 5) Non-linear effects in whistler wave propagation
- 6) Precipitation of charged particles from the radiation belts due to interaction with VLF waves.
- 7) VLF emissions triggered from the orbiting ACTIVE transmitter.
- 8) Comparison with emissions triggered by ground based VLF transmitters.

Alas, ACTIVE encountered several technical problems and the program was terminated. Nevertheless, when the em-radiating properties of spaceborne tethers will be finally assessed, some of the above objectives, namely 4, 5, 7 and 8 will greatly benefit. No further work has been done, however, in this direction. Some TSS investigations are currently addressing these questions.

6.2 Synergy

Some years ago, Lockheed-Martin, then Martin-Marietta, sponsored some studies to look into the synergy of tethers with other space missions, namely AFE (Aeroassist Flight Experiment), cancelled by NASA in 1991, and TIMED (Thermosphere-Ionosphere-Mesosphere Energetic Dynamics). Prof. Hurlbut (see "Contacts" Section) performed the study and the results are shown in tables 1 and 2, respectively.

AFE was a research "pathfinder" for a geosynchronous, lunar and planetary earth return aerobraking spacecraft. Prof. Hurlbut indicated that a tethered system could accomplish almost fifty percent of AFE objectives by exploring a much greater altitude range for a longer duration than AFE was supposed to fly.

The study on TIMED aimed at determining which of its instruments could potentially fly on a pathfinder type tethered spacecraft. Note that the study of Lockheed-Martin on TIMED focused on one of its earliest configurations. The major finding of this study was that a tethered spacecraft could possibly validate instruments which were operated in the 130-140 Km altitude range.

Table 1. AFE VS. Tethered System

AFE Flight Experiment	Tethered System Applicability
1. Forebody-Aerothermal Characterization Experiment (FACE)	Heat-flux and skin temperature measurements at all altitudes will provide thermal accommodation coefficients and validations of models/codes.
2. Radiative Heating Experiment (RHE)	Possibly applicable - Needs further study.
3. Wall Catalysis Experiment (WCE)	An extension of (1) to provide valuable catalytic vs. low catalytic gas/surface interaction data.
4. Base Flow Heating Experiment (BFHE)	Spherical afterbody data will differ from aerobrake geometry but will be very valuable with added Aerostabilizer instrument data.
5. Afterbody Radiometry Experiment (ARE)	Possibly applicable - Needs further study.
6. Alternate Thermal Protection Materials (ATPM)	Possibly applicable - Needs further study.
7. Heat Shield Performance (HSP)	Possibly applicable - Needs further study.
8. Pressure Distribution/Air Data System (PD/ADS)	Measurement of static/dynamic pressures at multiple satellite locations extremely valuable.
9. Aerodynamic Performance Experiment (APEX)	Satellite with Aerostabilizer will acquire extremely important aero characterization data over a wide altitude range.
10. Rarefield-Flow Aerodynamics Measurement Experiment (RAME) (RAME)	Measurements of momentum transfer characteristics and aero parameters (CD, CL, etc.) combined with (1) extremely valuable for validation of existing predictive analytical programs.
11. Plasma, Ion and Electron Concentration Experiment (PIECE)	Possibly applicable - Needs further study.
12. Microwave Reflectometer Ionization Sensor (MRIS)	Probably N/A
13. Aft Flow Ionization Sensor (MRIS)	Probably N/A
14. Ion Mass Spectrometer Experiment (IMSE)	Measurements of species and total density extremely important for atmospheric modeling.

Table 2. TIMED - Tethered Pathfinder Synergy

Timed Flight Experiment	Tethered System Pathfinder
1. Fabry-Perot Interferometer	Probably N/A - Requires more study.
2. Neutral Mass Spectrometer	Applicable for gas composition, temperatures and transverse winds.
3. Ion Mass Spectrometer	Applicability although ion composition and drift velocities of secondary importance.
4. Langmuir Probe	Applicable for measurement of electron temperatures and ion/electron densities.
5. Ion Drift Meter and Retarding Potentiometer	Applicable for measurement of ion temperatures, velocities and densities.
6. UV Spectrometer	Applicable for measurement of O3, NO temperatures, Noctilucent clouds, aerosols, and other minor constituents.
7. Imaging Photometer	Possibly N/A - Requires more study.
8. Triaxial Accelerometer	Applicable as a high priority instrument.
9. Energetic Particle Analyzer	Probably N/A - Requires more study.
10. Global UV Airglow Imager	Probably N/A - Requires more study.
11. Solar EUV Spectrometer/UV Photometer	Probably N/A - Requires more study.
12. Vector Magnetometer	Applicable for magnetic field measurements
13. Near Infrared Spectrometer	Probably N/A - Requires more study.
14. Electric Field Detector/Plasma Wave Experiment	Probably N/A - Requires more study.
15. Infrared Limb Sounder	Probably N/A - Requires more study.
16. Fast Electron Spectrometer	Probably N/A - Requires more study.
17. Energetic Particle Spectrometer	Probably N/A - Requires more study.

SECTION 7.0 REFERENCES

7.1 General

Due to the large production of tether-related papers we have limited our search to works published in the scientific literature. We have also included the list of papers presented at the last tether conference held in Washington.

The proceedings of papers presented at the four international conferences on Tethers in Space as well as workshops can be found in:

- “Applications of Tethers in Space” Workshop held in Williamsburg, VA June 15-17, 1983. NASA Contract NAS8-35403.
- “Applications of Tethers in Space” Workshop held in Venice, Italy, October 15-17, 1985. NASA Conference Publication CP 2422.
- “International Conference of Tethers In Space”, held in Arlington, VA, September 17-19, 1986. Proceedings published by the American Astronautical Society in *Advances in The Astronautical Sciences*, Vol. 62, 1987
- ”Tether Dynamic Simulation Workshop”, held in Arlington, VA Sept 16 1986. NASA Conference Publication CP 2458.
- “Space Tethers for Science in the Space Station Era”, Conference held in Venice, October 4-8, 1987. Proceedings published by Societa’ Italiana di Fisica, Bologna, Italy, 1988 (ISBN 88-7794-016-6).
- “Tethers In Space Toward Flight”, Conference held in San Francisco, CA, May 17-19, 1989. Proceedings published by the American Institute of Aeronautics and Astronautics, 1989 (ISBN 0-930403-50-9).
- International Round Table on Tethers in Space”, held in Noordwijk, The Netherlands, September 28-30, 1994. ESA WPP-081.
- “Fourth International Conference on Tethers in Space”, held in Washington, DC, April 10-14, 1995. Published by Science and Technology Corporation, Hampton, VA.

7.2 Table of Contents of the Fourth International Conference on Tethers in Space

VOLUME I

Manuscripts Unavailable at Time of Publication xix

General Information xxiii

FUTURE MISSIONS

Atmospheric Science with Tethers; Heating, Cooling and Chemistry in the
Lower Thermosphere 3

Kate P. Kirby, Smithsonian Astrophysical Observatory

Future of Tethers in Space 11

Mario D. Grossi, Smithsonian Astrophysical Observatory

DEMONSTRATED TECHNOLOGY

TSS-1 vs. TSS-1R 27

Bruno Strim, Mario Pasta and Ettore Allais, Alenia Spazio S.p.A.

The First and Second Flights of the Small Expendable Deployer System (SEDS) 43

H. Frayne Smith, NASA, Marshall Space Flight Center

Plasma Motor-Generator (PMG) Flight Experiment Results 57

James E. McCoy, C. O'Neill, J. Stanley and T. Settecerci, NASA, Johnson Space Center; Mario D. Grossi and Robert D. Estes, Smithsonian Astrophysical Observatory, M. Dobrowolny, G. Vannaroni, E. Melchioni, C. Bonifazi, C. Cosmovici and L. Iess, IFSI-CNR; R. Jerry Jost, System Planning Corporation; R.C. Olsen, Naval Postgraduate School, D.C. Ferguson, R. Tolbert, D. Rau, Ira Katz (S-Cubed) and J. Lilley, NASA, Lewis Research Center, Joseph A. Carroll, Tether Applications, Inc.; G. Taconi, L. Mina and W. Goree, University of Genoa

APPROVED FUTURE MISSIONS

SEDS/SEDSAT Project Overview 85

James K. Harrison, NASA, Marshall Space Flight Center

The OEDIPUS-C Sounding Rocket Experiment 95

H. Gordon James, Communications Research Centre; J. Glen Rumbold, Canadian Space Agency

OVERVIEW

The NASA/ASI TSS-1 Mission: Summary of Results and Reflight Plans 107

W. John Raitt and D.C. Thompson, CASS, Center for Atmospheric and Space Sciences, Utah State University; N. Stone, NASA, Marshall Space Flight Center; M. Dobrowolny, Istituto di Fisica dello Spazio Interplanetario; C. Bonifazi, Agenzia Spaziale Italiana; B. Gilchrist and P.M. Banks,

Space Physics Research Lab, University of Michigan; D. Hardy and
M. Oberhardt, Phillips Laboratory, GPSP; S. Williams and P.R. Williamson,
STAR Laboratory, Stanford University

TSS Mission 1 Flight Dynamic Anomalies 119

Donald D. Tomlin and David K. Mowery, NASA, Marshall Space Flight
Center; Bruno Musetti and Bruna Cibrario, Alenia Spazio, S.p.A.

Flight Data from the First and Second Flights of the Small Expendable
Deployer System (SEDS) 133

Charles C. Rupp, NASA, Marshall Space Flight Center

Plasma Motor Generator Mission Report 149

R. Jerry Jost and Dean Chlouber, System Planning Corporation;
Thomas L. Wilson, Christine A. O'Neil and James E. McCoy,
NASA, Johnson Space Center

SEDSAT Tether Dynamics Research 165

Cheryl D. Bankston, NASA, Marshall Space Flight Center; *Dennis Ray Wingo*,
Center for Space Plasma and Aeronomic Research, University of Alabama
in Huntsville; Mark A. Stedham, Defense Intelligence Agency, Missile and
Space Intelligence Center

A Space Tether Experiment STEX 181

Larry L. Burgess, F.M. Kustas and F.J. Jarossy, Lockheed Martin Astronautics

Flight Results from the OEDIPUS-A Tethered Experiment 193

H. Gordon James, Communications Research Centre; George Tyc,
Bristol Aerospace Limited

Sub-Satellites for Aerothermodynamic Studies in the Lower Thermosphere 211

Frank C. Hurlbut, University of California at Berkeley

Space Tethers for Ionospheric-Thermospheric-Mesospheric Science-Report
on the 1994 International Summer Workshop, Ann Arbor, MI 221

Brian E. Gilchrist, L.M. Brace, and G.R. Carignan, Space Physics Research
Laboratory, University of Michigan; R. Heelis, University of Texas-Dallas,
Center for Space Science; W.J. Raitt, Utah State University, Center for
Atmospheric & Space Science; C. Rupp, NASA, Marshall Space Flight Center;
H.G. James, Communications Research Center; C. Bonifazi, Agenzia Spaziale
Italiana; K-I Oyama, ISAS; G. Wood, NASA, Langley Research Center

Summary and Conclusions from the International Round Table on Tethers
in Space-ESTEC, September 1994 227

Mauro Novara, ESA/ESTEC

TSS-1 ELECTRODYNAMICS

TSS-1 SETS and CORE Experiment Results and Plans for Reflight 239

Brian E. Gilchrist, Peter M. Banks, Sven G. Bilén and Nestor R. Voronka,
University of Michigan, Space Physics Research Laboratory; Carlo Bonifazi,
Agenzia Spaziale Italiana; Don C. Thompson and W. John Raitt, Utah State
University, Center for Atmospheric and Space Science; Victor M. Agüero,
Scott D. Williams and Anthony C. Fraser-Smith, Stanford University,
EERA/STARLAB

Transient Response of the TSS System in the Ionosphere	253
<i>Sven G. Bilén and Brian E. Gilchrist, University of Michigan, Space Physics Research Laboratory; Enrico Melchioni and Marino Dobrowolny, Consiglio Nazionale delle Ricerche, Istituto di Fisica dello Spazio Interplanetario</i>	
Thruster Pickup Ions Detected by SPREE During TSS 1	267
<i>Louise C. Gentile, Boston College Institute for Space Research; W.J. Burke, J.S. Machuzak, David A. Hardy and D.E. Hunton, Phillips Laboratory</i>	
Electron Beam Propagation Observed During TSS 1	283
<i>David A. Hardy, Marilyn R. Oberhardt and William J. Burke, Phillips Laboratory/GPSG; Donald C. Thompson and W. John Raitt, Center for Atmospheric and Space Sciences, Utah State University; Louise C. Gentile, Boston College Institute for Space Research</i>	
Correlator Measurements of MHz Wave-Particle Interactions During TSS 1 Electron Beam Operations	299
<i>M. Paul Gough, Space Science Centre, University of Sussex; David A. Hardy, Marilyn R. Oberhardt and William J. Burke, Phillips Laboratory; Louise C. Gentile, Boston College Institute for Space Research</i>	
Observations of Ionosphere Heating in the TSS-1 Subsatellite Presheath	315
<i>Ira Katz and Myron Mandell, S-Cubed Division of Maxwell Laboratories; Enrico Melchioni, Istituto di Fisica dello Spazio Interplanetario; Marilyn Oberhardt, Phillips Laboratory, Space Sciences Laboratory; Don Thompson, Utah State University; Torsten Neubert and Brian Gilchrist, University of Michigan; Carlo Bonifazi, Agenzia Spaziale Italiana</i>	
Induced Ionospheric Double Probe Tether Potential Measurements and Models for TSS-1 Electrodynamics	331
<i>Scott D. Williams and V.M. Agüero, Stanford University; Donald C. Thompson and W. John Raitt, Center for Atmospheric and Space Sciences, Utah State University; Brian E. Gilchrist, Peter M. Banks and Nestor Voronka, Space Physics Research Laboratory, University of Michigan</i>	
Current-Voltage Characteristics of the Tethered Satellite	347
<i>U. Guidoni, and M. Dobrowolny, Agenzia Spaziale Italiana; E. Melchioni and G. Vannaroni, Istituto di Fisica dello Spazio Interplanetario - CNR, J.P. Lebreton, ESA/ESTEC</i>	
Identification of Charge Carriers in the Ionospheric Branch of the TSS-1 Tether_Generated Current System	359
<i>N.H. Stone, NASA, Marshall Space Flight Center; K. Wright, The University of Alabama in Huntsville; J.D. Winningham and C. Gurgiolo, Southwest Research Institute; U. Samir, Tel Aviv University; C. Bonifazi, Italian Space Agency; B. Gilchrist, The University of Michigan; M. Dobrowolny, Istituto Fisica Spazio Interplanetario/CNR</i>	
TSS-1 DYNAMIC OPERATIONS	
Deployer Performance Results for the TSS-1 Mission	375
<i>Leland S. Marshall and Ronald V. Geiger, Martin Marietta Astronautics</i>	
Long Period Tension Variations in TSS-1 and SEDS-2	389

Gordon E. Gullahorn, Mario Cosmo, Harvard-Smithsonian Center for Astrophysics;
Robert G. Hohlfeld, Metropolitan College, Boston University

TSS-1 Mission: Sub-Satellite Attitude Reconstruction 399

Bruno Musetti, Bruna Cibrario, Maria Stella Di Raimondo, and Paolo Martella,
Alenia Spazio S.p.A.

Simulation of TSS Passive Skiprope Damper 409

Jay N. Estes, NASA, Johnson Space Center, *David D. Lang*, Lang Associates

Active and Passive Damping of Tethered Systems 419

Francesco Angrilli, G. Bianchini and R. Da Forno, University of Padova;
G. Fanti, University of Parma

TSS-1 Tether Damping. Has Anything Been Learnd? 433

S. Bergamaschi, G. Carletti and P. Lion Stoppato, University of Padova

A Complex, Frequency Domain Skiprope Observer for Tethered Satellites 441

John R. Glaese, Control Dynamics

Transform Domain Based Observation and Prediction of Tether Skiprope

Oscillations for the TSS-1 Flight Experiment 455

Stephen M. Rodrigue, Abolfazl M. Amini, *George E. Ioup* and Juliette W. Ioup,
Department of Physics, University of New Orleans; Stan N. Carroll,
D. Keith Mowery and Don D. Tomlin, NASA, Marshall Space Flight Center

A Review of TSS Thermomechanical Properties in the Light of Preliminary

Experimental Results 469

F. Angrilli, *G. Bianchini* and S. Debei, Dipartimento di Ingegneria Meccanica,
Università di Padova; G. Fanti, Dipartimento di Ingegneria Industriale,
Università di Parma

Assessment of Shuttle Plume Effects on the Tethered Satellite System-1 489

Palmer B. Chiu, NASA, Johnson Space Center; Bill C. O'Donnell,
LinCom Corporation

SPONSORED PROJECTS

Reflight of the Tethered Satellite System Mission 507

Becky C. Soutullo, NASA, Marshall Space Flight Center

An Acquisition System to Reveal Ground E.M. Emissions from TSS1-R 515

Cinthy Ottone, Dipartimento di Ingegneria Biofisica ed Elettronica -
University of Genoa; S. Pagnan, Istituto di Automazione Navale -
National Research Council of Italy

A Ground-Based Receiving System for the Detection of Signals from the

Tethered Satellite System 527

S.T. Noble and W.E. Gordon, Rice University; R.D. Estes and
M.D. Grossi, Harvard-Smithsonian Center for Astrophysics

Breadboard Test and Flight Preparation of the RAPUNZEL Mission 535

D. Sabath, Fachegebiet Raumfahrttechnik; C. Kessler and M. Krischke,
Kayser-Trede GmbH; V.L. Balakin and V. Shachmistov,
Samara State Aerospace University

SEDS/SEDSAT Mission Plans	543
<i>Charles C. Rupp</i> , NASA, Marshall Space Flight Center; <i>William J. Webster, Jr.</i> , NASA, Goddard Space Flight Center	
Dynamics and Control of SEDSAT Deployment	551
<i>E.C. Lorenzini</i> , Harvard-Smithsonian Center for Astrophysics; <i>D.K. Mowery</i> and <i>C.C. Rupp</i> , NASA, Marshall Space Flight Center	
Sensitivity Analysis of SEDSAT Orbital Injection	563
<i>J. Peláez Alvarez</i> , E.T.S.I. Aeronáuticos, Universidad Politécnica de Madrid; <i>Enrico C. Lorenzini</i> , Harvard-Smithsonian Center for Astrophysics	
Design Considerations for a Long-Lifetime Space Tether	577
<i>F.M. Kustas</i> , <i>F.J. Jarossy</i> and <i>L.L. Burgess</i> , Lockheed Martin Astronautics Company	

VOLUME II

SMALL EXPENDABLE DEPLOYER SYSTEM (SEDS)

SEDS Deployer Design and Flight Performance	593
<i>Joseph A. Carroll</i> , Tether Applications	
Development of the SEDS EMP Tensiometer and Tether Attachment Mechanism	601
<i>Ray D. Rhew</i> , NASA, Langley Research Center	
SEDS End Mass Payload Magnetometer Engineering Performance and Rotational Data Analysis Results	613
<i>John H. Stadler</i> , NASA, Langley Research Center	
Design of the Signal and Power Conditioning Subsystems for the SEDS End Mass Payloads	627
<i>John K. Diamond</i> , NASA, Langley Research Center; <i>Wendy G. Nagurny</i> , Lockheed Engineering and Science Company	
SEDS Tether Deployment Ground Tests	653
<i>Bruce K. Wallace</i> , NASA, Marshall Space Flight Center	
SEDS-II Deployment Control Law and Mission Design	669
<i>Enrico C. Lorenzini</i> , Harvard-Smithsonian Center for Astrophysics; <i>D.K. Mowery</i> and <i>C.C. Rupp</i> , NASA, Marshall Space Flight Center	
The Small Expendable Deployer System (SEDS) Missions 1 and 2 Thermal Analysis and Flight Data Comparison	685
<i>Sheryl L. Kittredge</i> , NASA, Marshall Space Flight Center	
Data Reduction and Validation in a Small Project Environment: The SEDS-1, PMG and SEDS-2 Cases	697
<i>Lee R. Huynh</i> and <i>P. Chewning Toulmin</i> , Hughes-STX Corporation; <i>William J. Webster, Jr.</i> , NASA, Goddard Space Flight Center	
The SEDS Data Server: Contents, Access Procedures, and Mechanisms	705
<i>William J. Webster, Jr.</i> , NASA, Goddard Space Flight Center; <i>Brian H. Kirouac</i> , Hughes-STX Corporation	

A Comparison of SEDS-2 Flight and Dynamics Simulation Results	711
<i>John R. Glaese</i> , Control Dynamics, Division of bd Systems	
Three-Dimensional Modal Development with Time and Tether Length as a Dynamics Diagnostic Tool for SEDS	721
<i>Juliette W. Ioup</i> , George E. Ioup and Stephen M. Rodrigue, University of New Orleans; George M. Wood, NASA, Langley Research Center	
Restitution of Tethered Satellites Systems Motion	731
R. Clédassou and <i>Sébastien Herbinier</i> , Centre National d'Études Spatiales	
Acceleration Levels and Dynamic Noise on SEDS End-Mass	747
<i>Mario L. Cosmo</i> , E.C. Lorenzini, G.E. Gullahorn, Smithsonian Astrophysical Observatory	
The Final Dynamic State of SEDS-2: A Determination of the Torsional Pendulum Period from the Subsatellite Magnetometer Data	761
<i>Christopher D. Blunk</i> and Brian D. Humphry, Eleanor Roosevelt High School; Michael R. Douglass, University of North Carolina at Chapel Hill; William J. Webster, Jr., NASA, Goddard Space Flight Center; George H. Strachan, Eleanor Roosevelt High School	
Visualization of the Motion of the SEDS 1 and 2 Subsatellites	767
<i>Michael Douglass</i> , University of North Carolina at Chapel Hill; P. Chewning Toulmin and Lee R. Huynh, Hughes-STX Corporation; William J. Webster, Jr., NASA, Goddard Space Flight Center	
Analysis of Video Images of the Re-entry of the SEDS-I End Mass	773
<i>David L. Talent</i> , Lockheed Engineering and Sciences Company	
The Visual Brightness of the SEDS-2 Tether	795
<i>William J. Webster, Jr.</i> , James J. Butler, James T. McLean, Locke M. Stuart, NASA, Goddard Space Flight Center; G. Si, Swales and Associates	
Ground Radar Data and Optical Measurements - SEDS, PMG, and SEDS-2	815
<i>Thomas J. Settecerry</i> , Lockheed Engineering and Sciences Company	
Comparison of Predicted and Actual Orbital Lifetimes for the SEDS-2 Mission	837
<i>Steven W. Evans</i> , NASA, Marshall Space Flight Center	
Micro-Meteoroid and Orbital Debris Damage Analyses on SEDS Tether	847
<i>Kazuo Ben Hayashida</i> , Jennifer H. Robinson and Scott A. Hill, NASA, Marshall Space Flight Center	

ELECTRODYNAMICS

Characteristics of Plasma Contactors for Spacecraft Charging Control	861
<i>Paul J. Wilbur</i> and J. Steven Snyder, Colorado State University	
Plasma Contactor Device Family for Space Use Working Up to 10 A: Review of the Functional Testing Activity	873
<i>M. Minucci</i> , A. Severi and M. Capacci, Proel Technologie; C. Bonifazi and F. Svelto, ASI	

- Current Collection Enhancement by Neutral Gas Emissions Into a Plasma 881
L. Conde and *L. León*, E.T.S.I. Aeronáuticos,
 Universidad Politécnica de Madrid
- Ionization in An Electron Collecting Contactor 889
Eduardo Ahedo, E.T.S.I. Aeronáuticos, Universidad Politécnica de Madrid;
M. Martínez-Sánchez, Department of Aeronautics and Astronautics, M.I.T.
- Stability Model for Plasma Contactors 897
V. Lapuerta and *E. Ahedo*, E.T.S.I. Aeronáuticos,
 Universidad Politécnica de Madrid
- Plasma Contactors for Electrodynamic Tether Sysetsm 903
Igor A. Beznos and *Konstantin N. Kozubsky*, "Fakel" Enterprise;
Alexei S. Isakov and *Vladimir Kim*, Research Institute of Applied Mechanics
 and Electrodynamics of Moscow Aviation Institute
- Central Problem of Space Electronics and Electrodynamic-TSS 909
N.A. Savich, Institute of Radio Engineering and Electronics of the
 Russian Academy of Sciences
- RMHD-Simulation of An Electrodynamic Tethered Satellite System
 in the Ionosphere 921
Andreas Schröer, Ruhr-Universität Bochum
- Current Closure for a Tethered Satellite System 935
Chia-Lie Chang and *Adam Drobot*, Science Applications
 International Corporation; *Konstantinos Papadopoulos*,
 University of Maryland
- Campaigns of Ground Listening to the E.M. Emissions Expected 949
 from Spaceborne Electrodynamic Tether Systems
G. Tacconi, *S. Dellepiane* and *C. Ottonello*, University of Genoa DIBE;
S. Pagnan and *L. Minna*, IAN/CNR National Research Council; *M.D. Grossi*,
 SAO Harvard-Smithsonian Astrophysical Observatory
- A High Perveance Electron Generator with ON/OFF Modulation Capabilities for
 Current Up to 1 A 965
M. Minucci, *G. Noci* and *A. Severi*, Proel Technologie; *C. Bonifazi* and
F. Svelto, ASI
- Alfven Wave Signature from Constant-Current Tethers 973
Robert D. Estes, Harvard-Smithsonian Center for Astrophysics;
Jaun R. Sanmartín, ETSI Aeronáuticos, Universidad Politécnica de Madrid
- Nonreciprocal Magnetoplasma Sheath Waves on Structures in Space 983
Andrea A.E. Lüttgen and *Keith G. Balmain*, University of Toronto
- The Space-Charge Effect on Current Collected by a Spherical Probe in a
 Magnetized Plasma 993
Weiwei Li and *J.G. Laframboise*, Department of Physics and Astronomy,
 York University
- PIC Simulation of Spherical-symmetric Active and Passive High
 Voltage Discharges 1009
Hartmut Marschall and *F.M. Neubauer*, Universität zu Köln

On the Creation of Space Charges in the Flux Tubes of Electrodynamic
Tethers in Space 1019

R.L. Stenzel and *J.M. Urrutia*, Department of Physics,
University of California

The Magnetic Presheath of a Positively Charged Spacecraft:
Estimating Its Potential 1025

J.G. Laframboise, Physics and Astronomy Department, York University;
L.J. Sonmor, Institute for Space and Atmospheric Studies, University
of Saskatchewan; *B.A. Whalen*, Herzberg Institute of Astrophysics,
National Research Council

The Use of Electron Beam Experiments on Orbiting Tethered Platforms for
Remote Sensing of E_{\perp} in the Auroral Acceleration Region: The Active
Magnetospheric Particle Acceleration Satellite (AMPAS) 1035

Linda A. Habash, Torsten Neubert and Brian E. Gilchrist, University
of Michigan; *W. John Raitt*, Utah State University

An Extended Electron Beam for Auroral Studies 1045

Manuel Martinez-Sanchez, Department of Aeronautics and Astronautics, MIT;
Jaun R. Sanmartin, ETSI Aeronauticos, Universidad Politecnica de Madrid

An Investigation of Forces in a Shielded Conductor 1067

C.H. Spenny, *C. O'Dell* and *W.F. Bailey*, Air Force Institute of Technology

TETHER TECHNOLOGY

SEDS Characteristics and Capabilities 1079

Joseph A. Carroll and *John C. Oldson*, Tether Applications

ESA Development on Expendable Tether Mechanism Technology 1091

Renato Licata, Alenia Spazio S.p.A.; *J. Miguel Gavira*, ESA-ESTEC

Tether System Applications in Support of Large Space Infrastructures 1101

Luigi Bussolino, *Pietro Merlina* and *Maria Antonietta Perino*, Alenia Spazio S.p.A.

Tethered Re-Entry Application Deployment Control 1107

Renato Licata, Alenia Spazio S.p.A.

Rotating Space Station for Out-Of-Plane Orbital Transfer Using Tethers 1119

Bruce A. Mackenzie, Space Studies Institute

System Engineering and Integration (SE&I) Aspects for a Tether
Application at the ISSA 1133

Paul Tetzlaff, DASA/RST Rostock Raumfahrt und Umweltschutz

Adaptive Attitude Control for the Base Platform of a Tethered System
with Fuzzy Logic 1143

W. Hallmann, *E. Plescher* and *W. Zahnnow*, Fachhochschule Aachen,
Space Department

Failsafe Multistrand Tether SEDS Technology 1151

Robert P. Hoyt and *Robert L. Forward*, Tethers Unlimited

Temperature Behavior of Tethers in Orbit 1161

W. Hallmann, *B. Justen* and *E. Plescher*, FH Aachen, Space Department

- Effects of Debris Damage on New Long-Life Tethers 1171
F. Angrilli, G. Bianchini, R. Da Forno, S. Debei and B. Saggin,
 Center Of Study and Space Activities "G. Columbo", CISAS, University
 of Padova; G. Fanti, Department of Industrial Engineering,
 University of Parma
- Stress Distribution Measurements in Composite Space Ropes 1181
Giulio Fanti, Dipartimento di Ingegneria Industriale, Università di Parma
- Termination Methods for Synthetic Fiber Tethers 1195
Douglas P. Bentley, Cortland Cable Company
- The Progress-M Based Sample & Material Re-Entry Demonstration 1203
Pietro Merlina, Alenia Spazio S.p.A.; Peter Schwebke, DASA-RST;
 Mauro Novara, ESA-ESTEC
- An Analytic Characterization of the Optimal Mass Problem
 for Aerobraking Tethers 1217
Steven G. Tragesser and James M. Longuski, Purdue University;
 Jordi Puig-Suari, Arizona State University
- Tether Survivability: SEDS-2 As A Diagnostic Tool 1233
Martin Beech, The University of Western Ontario; P. Chewning Toulmin,
 Hughes-STX Corporation

TETHER SCIENCE

- Expected Magnetic Field Results from a Tether Mission 1245
Patrick T. Taylor, NASA Goddard Space Flight Center; Joy A. Conrad,
 Hughes STX Corporation; James J. Frawley, Herring Bay Geophysics
- Tethered Systems in the Magnetospheric Studies 1259
Stanislav I. Klimov, Anatoly A. Petrukovich, Mikhail L. Pivovarov,
 Andrey V. Prudkoglyad, Vjacheslav G. Rodin, Alexander A. Skalsky,
 Space Research Institute (IKI) Russian Academy of Science;
 Valery E. Korepanov, Special Design Division of
 National Academy of Sciences of Ukraine
- Spectroscopic Measurements from a Tethered Satellite Platform 1269
Kelly V. Chance, Harvard-Smithsonian Center for Astrophysics
- Gravity Gradiometry from the Downward Tethered Satellite System 1273
Franco Fuligni, V. Iafolla and S. Nozzoli, Istituto di Fisica dello Spazio
 Interplanetario; M. Cosmo, M.D. Grossi, G.E. Gullahorn and E. Lorenzini,
 Harvard-Smithsonian Center for Astrophysics
- Analysis of a Dumbbell Sensor for Space Gradiometry 1281
Simone B. Bortolami, M.G.H. Biomotion Lab - Harvard Medical School;
 F. Angrilli, University of Padova; C. Jekeli, Ohio State University;
 M.D. Grossi, Harvard-Smithsonian Center for Astrophysics

VOLUME III

DYNAMICS

A New Full Non-Linear Model of the Tethered Satellite Systems
Based on the Characteristics Method 1299

F. Angrilli, *R. Da Forno* and B. Saggin, University of Padova

Dynamics of Low-Tension Spinning Tethers 1309

A. Misra and M. Keshmiri, McGill University; V.J. Modi, University of B.C.;
G. Tyc and R. Han, University of Manitoba; F. Vigneron and A. Jablonski,
Canadian Space Agency

Resonant Conditions for a Stretched Spinning Tether 1325

Ray P.S. Han and Albert C.J. Luo, University of Manitoba

Analytical Solutions for a Model of a Spinning Tether 1341

Thomas G. Berry and Joseph J. Williams, University of Manitoba

Severed Tether Dynamics and Probability 1353

Kenneth J. Welzyn and Jennifer H. Robinson, NASA,
Marshall Space Flight Center

Dynamics of a Space Tethered Satellite System with Two Rigid Endbodies 1367

W. Steiner, A. Steindl and H. Troger, Technical University Vienna

Attachment Point Motion for Active Damping of Vibrations in Tethered
Artificial Gravity Spacecraft 1381

Shannon L. Thornburg and J. David Powell, Stanford University

Simultaneous Attitude and Vibration Control of Tethered Satellite Systems 1395

S. Pradhan and *V.J. Modi*, The University of British Columbia;
A.K. Misra, McGill University

Deployment and Retraction of a Continuous Tether: The Equations Revisited 1415

F.L. Janssens, D. Poelaert and E.B. Crellin, European Space Research and
Technology Center (WMM)

Attitude Maneuvers of a Flexible Space Station by Means of Deployable Tethers 1425

Franco Bernelli-Zazzera, Amalia Ercoli-Finzi and P. Mantegazza,
Dipartimento di Ingegneria Aerospaziale, Politecnico di Milano

Optimal Mass Flexible Tethers for Aerobraking Maneuvers 1441

Jordi Puig-Suari, Arizona State University

Atmospheric Research Using Tethered Satellite Systems in Elliptic Orbits 1451

Howard A. Flanders and Penny L. Niles, Martin Marietta Astronautics

Constrained Iterative Spectral Deconvolution for Analysis of Closely Spaced
Modal Peaks in the Fourier Transform of Tethered Satellite Dynamics Data 1461

Abolfazl M. Amini, Southern University, Baton Rouge and University of
New Orleans; *George E. Ioup* and Juliette W. Ioup,
University of New Orleans

An Extended Kalman Filter for Observing the Skiprope Phenomenon of the
Tethered Satellite System 1475

Haik Biglari, Sverdrup Technology, Inc.; Zachary J. Galaboff, NASA,
Marshall Space Flight Center

Validation of Analytical Modeling of OEDIPUS Tethers Using Experimental
Results from TE-LAB 1483

F.R. Vigneron, A.M. Jablonski and R. Chandrashaker, Canadian
Space Agency; B. McClure, J. Bergmans and D. Staley, Carleton University;
G. Tyc, Bristol Aerospace Limited

NEAR FUTURE

An Update to Proposed Space Tether Applications for International
Space Station Alpha 1501

Donald S. Crouch, A. Colton Park and Gilbert M. Kyrias, Martin Marietta
Astronautics; Bruno Strim, Saverio Lioy, Gene Compton (NASA Rep), Alenia
Spazio S.p.A.; Andrea Lorenzoni, Agenzia Spaziale Italiana; Carolyn Conley,
Muniz Engineering

A Proposed Shuttle-Tethered Satellite System Atmospheric Verification Mission 1513

Donald S. Crouch, Howard A. Flanders and Gilbert M. Kyrias,
Martin Marietta Astronautics

AIRSEDS-ITM: A Proof-of-Concept Tether Mission Into the Earth's
Upper Atmosphere 1527

Andrew D. Santangelo, The Michigan Technic Corporation; Terrance G. Onsager
and Craig A. Kletzing, University of New Hampshire

Dual Tethered Satellite Systems for Space Physics Research 1543

Penny L. Niles, Martin Marietta Astronautics; Brian E. Gilchrist, University
of Michigan; Jay N. Estes, NASA, Johnson Space Center

AIRSATT-Atmospheric/Ionospheric Research Satellite Using Advanced
Tether Technology 1559

B.E. Gilchrist, J. Dodds, B.C. Kennedy, University of Michigan; P.L. Niles,
Martin Marietta Astronautics; C.C. Rupp, NASA, Marshall Space Flight Center

Tethered Multi_Probe for Thermospheric Research 1567

E.C. Lorenzini, M.L. Cosmo, M.D. Grossi, K. Chance and J.L. Davis,
Harvard-Smithsonian Center for Astrophysics

Alenia Spazio Long Term Commitment to Space Tethers: Past, Present and Future 1577

Paolo Piantella and Francesco Giani, Alenia Spazio S.p.A.

Space Research in the BICEPS Experiment 1585

H. Gordon James, Communications Research Centre; Andrew W. Yau,
NRCC Herzberg Institute of Astrophysics; George Tyc,
Bristol Aerospace Limited

A Shuttle Deployed Tether Technology Demonstration Mission to Serve
Canadian and United States Needs 1599

G. Tyc, Bristol Aerospace Limited; C.C. Rupp, NASA, Marshall Space
Flight Center; A.M. Jablonski and F.R. Vigneron, Canadian Space Agency

What Is Necessary to Get Your Ideas to NASA 1611

Patricia M. Doty, NASA, Marshall Space Flight Center

FAR FUTURE

- Synthetic Aperture Radar Interferometry by Means of Tethered Antennas 1631
Antonio Moccia and Marco D'Errico, Università degli Studi di Napoli;
Sergio Vetrella, Seconda Università degli Studi di Napoli

The Electromagnetic Clean Subsatellite SPELIS for Studies on Plasma-Wave Phenomena Caused by Operations of the Electrodynamical Tethered System in Space Plasmas 1643
Stanislav I. Klimov, Yuri N. Agafonov, Alexander A. Skalsky and Vyacheslav G. Rodin, Space Research Institute of the Russian Academy of Science

Methods of Deployment of the Polymodule Tether System with Utilization of the Converted Ballistic Missile Separation Block 1653
Gennady V. Malyshev, L.M. Kalashnikov, V.M. Kulkov, N.N. Markin and A.P. Svtin, Research Institute of Applied Mechanics and Electrodynamics of Moscow Aviation Institute; V.M. Ivanov and V.I. Mironov, Central Research Institute of Machine Building; N.A. Obukhov, Makeev Design Office of Mechanical Engineering

Optimization of a Low Altitude Tethered Probe for Martian Atmosphere Dust Collection 1663
Monica Pasca, Università di Roma "La Sapienza"; Enrico Lorenzini, Harvard-Smithsonian Center for Astrophysics

AIRSEDS-II™: A TSS-2 Precursor Mission to Test and Demonstrate Tethered Systems in the Earth's Upper Atmosphere 1675
Andrew D. Santangelo, The Michigan Technic Corporation

Optimal De-spinning and Retrieval of a Tethered Artificial Gravity Spacecraft 1685
Salma I. Saeed and J. David Powell, Stanford University

Tethered Stabilized Platform Attitude Control by Moving the Attachment Point Influence of Tether Transverse Vibration 1697
Francesco Angrilli, R. Da Forno, G. Bianchini, B. Saggin, University of Padova; G. Fanti; University of Parma

Future Tether Missions in Space: A European Perspective 1705
Luigi Bussolino, Pietro Merlina and Maria A. Perino, Alenia Spazio S.p.A.

A Digital Robust Controller for a Tethered Reflector/Antenna System 1721
Peter M. Bainum and Zhaozhi Tan, Howard University

A Skyhook from Phobos to Mars 1737
William B. Thompson, University of California at San Diego;
Martin O. Stern, California Space Institute, Scripps Institution of Oceanography

SOUNDING ROCKETS

Design of the OEDIPUS-C Suborbital Tethered Payload 1749
W. Eliuk, R. Rob, G. Tyc and I. Walkty, Bristol Aerospace Limited;
G. Rumbold, Canadian Space Agency; H.G. James, Communications Research Centre

Space Plasma Experiments with the Tethered OEDIPUS-C Payload 1765
H. Gordon James, Communications Research Centre; Keith G. Balmain,
University of Toronto

Tethered-Probe Measurements of ECHO 7 Charging-Discharging 1781
William J. Burke and George P. Murphy, Phillips Laboratory;
Perry R. Malcolm, USAF Academy

Design, Qualification and Calibration of the Tether Force Sensor (TFS)
for the OEDIPUS-C Mission 1793
G. Tyc, W.R. Whitehead and J.L. Phillips, Bristol Aerospace Limited;
J.G. Pierson, Pierson Associates Incorporated; A.M. Jablonski and
F.R. Vigneron, Canadian Space Agency

Tether Laboratory Demonstration System (TE-LAB) A Ground Test Facility
for the OEDIPUS Tether Missions 1809
Alexander M. Jablonski, Frank R. Vigneron and Rajagopalan Chandrasher,
Canadian Space Agency; John L. Bergmans, Bruce A. McClure and
Douglas A. Staley, Carleton University; George Tyc, Bristol Aerospace Limited

Experimental Investigation of the Dynamics of Spinning Bodies 1823
V.J. Modi, S. Pradhan and M. Chu, University of British Columbia; G. Tyc,
Bristol Aerospace Limited; A.K. Misra, McGill University

Sounding Rocket Tethered Payload Experiments: The NASA Charge Program 1837
W. John Raitt, CASS, Utah State University

PLASMA MOTOR GENERATOR (PMG)

Comparison of Theoretical Predictions with Plasma Motor Generator (PMG)
Experimental Data 1847
John R. Lilley, Jr., Agnes Greb, *Ira Katz* and Victoria A. Davis,
S-Cubed Division of Maxwell Laboratories; James E. McCoy, NASA,
Johnson Space Center; Joel Galofaro and Dale C. Ferguson, NASA,
Lewis Research Center

Correlation of Tether Current with Day/Night Cycles During PMG Mission 1857
Dean Chlouber and R. Jerry Jost, System Planning Corporation;
Thomas L. Wilson, NASA, Johnson Space Center;

Comparison of Remote-Sensor Determination of PMG Two-Body Dynamics
with Telemetry-Inferred Tether Dynamics 1873
Dean Chlouber and R. Jerry Jost, System Planning Corporation;
Thomas L. Wilson and James E. McCoy, NASA, Johnson Space Center

VHF Radar Measurements of PMG Ionospheric Interactions 1875
R. Jerry Jost and Dean Chlouber, System Planning Corporation

Ionosphere-Thermosphere Coupling with Large-Amplitude, Nonlinear
Ion-Acoustic Solutions Triggered by Electrified Spacecraft 1877
R. Jerry Jost and *Dean Chlouber*, System Planning Corporation;
Thomas L. Wilson, NASA, Johnson Space Center

Hawaii-Hilo Ground Observations on the Occasion of the PMG Flight of
June 23, 1993: Further Spectral Analysis 1879
Cinthyia Ottonello and Giorgio Tacconi, Dipartimento di Ingegneria Biofisica

ed Elettronica-University of Genoa; Sergio Pagnan, Istituto di Automazione
Navale - National Research Council of Italy; Luca Mina, Advanced
Engineering Technology - Torre A Corte dei Lambruschini

Electrodynamic Interactions Between the PMG Tether and the Magneto-Ionic
Medium of the Ionosphere 1891

Mario D. Grossi and Robert D. Estes, Harvard-Smithsonian Center
for Astrophysics; *James E. McCoy*, NASA, Johnson Space Center

Tether Current-Voltage Characteristics 1899

R.C. Olsen, Chung-Jen Chang and Chia-Hwa-Chi, Naval Postgraduate School

APPENDIX A

Author Index 1923

APPENDIX B

Attendee List 1929

7.3 Bibliography

Alfven, H., "Spacecraft Propulsion: New Methods," Science, Vol. 176, p. 167-168, 14 Apr. 1972.

Allais, E. and Bergamaschi, S., "Dynamics of Tethered Satellites: Two Alternative Concepts for Retrieval," Meccanica, Vol. 14, No. 2, p. 103-111, June 1979.

Alpert, Ya. L., "On Some Electromagnetic Phenomena in the Tether Magnetoplasma Cloud," Nuovo Cimento C, Serie 1, Vol. 14C, September-October 1991.

Anderson, J., Wood, W., Siemers, P., Research at the Earth's Edge," Aerospace America, Vol. 26, No. 4, pp. 30-32, April 1988.

Anderson, K. S., Hagedorn, Peter, "Control of Orbital Drift of Geostationary Tethered Satellites," Journal of Guidance, Control and Dynamics, Vol. 17, No. 1, p. 10-14, February 1994.

Anderson, L. A., "Tethered Elevator Design for Space Station," Journal of Spacecraft and Rockets, Vol. 29, p. 233-238, March-April 1992.

Anderson, W. W., "On Lateral Cable Oscillations of Cable-Connected Space Stations," NASA TN 5107, Langley Research Center, Hampton, Virginia, Mar. 1969.

Angrilli, F., Bianchini, G., Da Lio, M., Fanti, G., "Modelling the mechanical Properties and Dynamics of the Tethers for the TSS-1 and TSS-2 Missions", ESA Journal, Vol. 12, p. 353-368, 1988

Arnold, D. A., "The Behavior of Long Tethers in Space," Journal of the Astronautical Sciences, Vol. 35, No. 1, p. 3-18, January-March, 1987.

Ashenberg, J. and Lorenzini, E.C., "Dynamics of a Dual-Probe Tethered System," Journal of Guidance, Control and Dynamics, Vol. 20, No. 6, p. 1265-1268, 1997.

Austin, F., "Nonlinear Dynamics of a Free-Rotating Flexibly Connected Double-Mass Space Station," Journal of Spacecraft and Rockets, Vol. 2, No. 6, p. 901-906, 1965.

Austin, F., "Torsional Dynamics of an Axially Symmetric, Two-Body Flexibly Connected Rotating Space Station," Journal of Spacecraft and Rockets, Vol. 2, No. 6, p. 626-628, 1965.

Bainum, P. M., and Evans, K. S., "Gravity-Gradient Effects on the Motion of Two Rotating Cable-Connected Bodies," AIAA Journal, Vol. 14, No. 1, p. 26-32, 1976.

Bainum, P. M., and Evans, K. S., "Three Dimensional Motion and Stability of Two Rotating Cable-Connected Bodies," Journal of Spacecraft and Rockets, Vol. 12, No. 4, p. 242-250, 1975.

Bainum, P. M., and Kumar, V. K., "Optimal Control of the Shuttle-Tethered System," Acta Astronautica, Vol. 7, No. 12, p. 1333-1348, May 1980.

Bainum, P. M., Diarra, C. M., and Kumar, V. K., "Shuttle-Tethered Subsatellite System Stability with a Flexible Massive Tether," AIAA J. Guidance, Control and Dynamics, Vol. 8, No. 2, p. 230-234, Mar.-Apr. 1985.

Bainum, P. M., Harkness, R. E. and Stuiver, W., "Attitude Stability and Damping of a Tethered Orbiting Interferometer Satellite System," The Journal of Astronautical Sciences, Vol. 19, No. 5, p. 364-389, Mar-Apr. 1972.

Baker, W. P., Dunkin, J. A., Galaboff, Z. J., Johnson, K. D., Kissel, R. R., Rheinfurth, M. H., and Siebel, M.P.L., "Tethered Subsatellite Study," NASA TM X-73314, NASA/MSFC, Mar. 1976.

Banerjee, A. K., and Kane, T. R., "Tether Deployment Dynamics," The Journal of Astronautical Sciences, Vol. 30, No. 4, p. 347-365, Oct-Dec 1982.

Banerjee, A. K., and Kane, T. R., "Tethered Satellite Retrieval with Thruster Augmented Control" Journal of Guidance, Control and Dynamics, Vol. 7, No. 1, p. 45-50, 1984.

Banerjee, A. K., "Dynamics of Tethered Payloads with Deployment Rate Control," Journal of Guidance, Control and Dynamics, Vol. 13, p. 759-762, July-August 1990.

Banks, P., et al, "The Tethered Satellite System; Final Report from the Facility Requirements Definition Team," NAS8-33383, MSFC, May 1980.

Bekey, I. "Tethers Open New Space Options," Astronautics and Aeronautics, Vol. 21, No. 4, p. 33-40, Apr. 1983.

Bekey, I., and Penzo, P. A., "Tether Propulsion," Aerospace America, Vol. 24, No. 7, p. 40-43, July 1986.

Beletskii, V. V. and Levin, E. M., "Dynamics of Space Tether Systems," Advances in the Astronautical Sciences, Vol. 83.

Beletskii, V. V., and Guivertz, M., "The Motion of an Oscillating Rod Subjected to a Gravitational Field," Kosmicheskie Issledovania, Vol. 5, No.6, 1967.

Beletskii, V. V., and Levin, E. M., "Dynamics of the Orbital Cable System," Acta Astronautica, Vol. 12, No. 5, p. 285-291, 1985.

Beletskii, V. V., and Levin, E. M., "Stability of a Ring of Connected Satellites," Acta Astronautica, Vol. 12, No. 10, p. 765-769, 1985.

Beletskii, V. V., and Navikova, E. T., "On the Relative Motion of Two Cable-Connected Bodies in Orbit," Cosmic Research, Vol. 7, No. 3, p. 377-384, 1969.

Beletskii, V. V., "On the Relative Motion of Two Cable-Connected Bodies in Orbit-II," Cosmic Research, Vol. 7, No. 6, p. 827-840, 1969.

Bergamaschi, S., "Tether Motion after Failure," Journal of Astronautical Sciences, Vol. 30, No. 1, p. 49-59, Jan.-Mar. 1982.

Bergamaschi, S. and Catinaccio, A., "Further Developments in the Harmonic Analysis of TSS-1," Journal of the Astronautical Sciences, Vol. 40, No. 2, p. 189-201, April-June 1992.

Bergamaschi, S. and Bonon, F., "Coupling of Tether Lateral Vibration and Subsattelite Attitude Motion," Journal of Guidance, Control and Dynamics, Vol. 15, No. 5, p. 1284-1286, September-October 1992.

Bergamaschi, S. and Bonon, F., "Equilibrium Configurations in a Tethered Atmospheric Mission," Acta Astronautica, Vol. 29, No. 5, p. 333-339, May 1993.

Bergamaschi, S., Bonon, F. and Legnami, M., "Spectral Analysis of Tethered Satellite System-Mission 1 Vibrations," Journal of Guidance, Control and Dynamics, Vol. 18, No. 3, p. 618-624, June 1995.

Bergamaschi, S., Zanetti, P. and Zottarel, C., "Nonlinear Vibrations in the Tethered Satellite System-Mission 1," Journal of Guidance, Control and Dynamics, Vol. 19, No. 2, p. 289-296, April 1996.

Birch, P., "Orbital Ring Systems and Jacob's Ladders," Journal of British Interplanetary Society, Vol. 35, No. 11, p. 474-497, Nov. 1982 (Part 1), Vol. 36, No. 3, p. 115-128, Dec. 1983 (Part 2).

Blinov, A. P., Dosybekov, K., "Perturbed Motions of a Dumbbell in a Central Newtonian Force Field," ISSN 0010-9525, Cosmic Research, Jan. 1988.

Bolotina, N. E., and Vilke, V. G., "Stability of the Equilibrium Positions of a Flexible, Heavy Fiber Attached to a Satellite in a Circular Orbit," Cosmic Research, Vol. 16, No. 4, p. 506-510, Jan. 1979.

Breakwell, J. V., Gearhart, J. W., "Pumping a Tethered Configuration to Boost its Orbit Around an Oblate Planet," Journal of the Astronautical Sciences, Vol. 35, No. 1, p. 19-40, January-March, 1987.

Breakwell, J. V., "Stability of an Orbiting Ring," Journal of Guidance and Control, Vol. 4, No. 2, p. 197-200, 1981.

Brown, K. G., Melfi, L. T., Jr., Upchurch, B.T. and Wood, G. M. Jr., "Downward-Deployed Tethered Satellite Systems, Measurement Techniques, and Instrumentation - A Review," Journal of Spacecraft and Rockets, Vol. 29, No. 5, p. 671-677, September-October 1992.

Bschorr, O., "Controlling Short-Tethered Satellites," Acta Astronautica, Vol. 7, p. 567-573, May 1980.

Carroll, J. A., "Tether Applications in Space Transportation," Acta Astronautica, Vol. 13, No. 4, p. 165-174, 1986.

Chang, C.L., Satya-Narayana, P., Drobot, A.T., Papadopoulos, L. and Lipatov, A.S., "Hybrid Simulations of Whistler Waves Generation and Current Closure by a Pulsed Tether in the Ionosphere," Geophysical Research Letters, Vol. 21, No. 11, p. 1015-1018, June 1, 1994.

Childs, D. W., and Hardison, T. L., "A Movable-Mass Attitude Stabilization System for Cable-Connected Artificial-g Space Stations," Journal of Spacecraft and Rockets, Vol. 11 No. 3, p. 165-172, 1974.

Chobotov, V. A., "A Synchronous Satellite at Less Than Synchronous Altitude," Journal of Spacecraft and Rockets, Vol. 13, No. 2, p. 126-128, 1976.

Chobotov, V. A., "Gravity-gradient Excitation of a Rotating Cable-Counterweight Space Station in Orbit," Journal of Applied Mechanics, Vol. 30, No. 4, p. 547-554, Dec. 1963.

Chu, C., and Gross, R., "Alfven Waves and Induction Drag on Long Cylindrical Satellites," AIAA Journal, Vol. 4, p. 2209, 1966.

Collar, A., and Flower, J., "A (Relatively) Low Altitude 24-Hour Satellite," J. British Interplanetary Society, Vol. 22, p. 442-457, 1969.

Colombo, G., Gaposchkin, E. M., Grossi, M. D., and Weiffenbach, G. C., "The 'Skyhook': A Shuttle-Borne Tool for Low Orbital Altitude Research," Meccanica, Vol. 10, No. 1, Mar. 1975.

Corso, G. J., "A Proposal to Use an Upper Atmosphere Satellite Tethered to the Space Shuttle for the Collection of Micro-Meteoritic Material," J. of the British Interplanetary Society, Vol. 36, p. 403-408, 1983.

Cotellessa, A. and DeMatteis, G., "Passive Stabilization of a Tethered System in Low Earth Orbit," Acta Astronautica, Vol. 29, No. 3, p. 169-180, March 1993.

- Crist, S. A., and Easley, J. G., "Cable Motion of a Spinning Spring-Mass System in Orbit," Journal of Spacecraft and Rockets, Vol. 7, No. 11, p. 1352-1357, 1970.
- Davis, W.R. and Banerjee, A.K., "Libration Damping of a Tethered Satellite by Yo-Yo Control with Angle Measurement," Journal of Guidance, Control and Dynamics, Vol. 13, p. 370-374, March-April 1990.
- Decou, A.B., "Orbital Dynamics of the Hanging Tether Interferometer," Journal of Guidance, Control and Dynamics, Vol. 14, p. 1309-1311, November-December 1991.
- DeMatteis, G. and DeSocio, Luciano M., "Stability of a Tethered Satellite Subjected to Stochastic Forces," Acta Astronautica, Vol. 25, p. 61-66, February 1991.
- DeMatteis, G., "Dynamics of a Tethered Satellite in Elliptical, Non-Equatorial Orbits," Journal of Guidance, Control and Dynamics, Vol. 15, No. 3, p. 621-626, May-June 1992.
- Denig, W.F., Maynard, N.C., Burke, W.J. and Maehlum, B.N., "Electric Field Measurements During Supercharging Events on the MAIMIK Rocket Experiment," Journal of Geophysical Research, Vol. 96, p. 3601-3610, March 1, 1991.
- Dobrowolny, M., Arnold, D., Colombo, G., and Grossi, M., "Mechanisms of Electrodynamical Interactions with a Tethered Satellite System and the Ionosphere," Reports in Radio and Geoastronomy, No. 6, Aug., 1979.
- Dobrowolny, M., "Electrodynamics of Long Metallic Tethers in the Ionospheric Plasma," Radio Science, Vol. 13, p. 417, 1978.
- Dobrowolny, M. and Melchioni, E., "Electrodynamical Aspects of the First Tethered Satellite Mission," Journal of Geophysical Research, Vol. 98, No. A8, p. 13,761-13,778, August 1, 1993.
- Dobrowolny, M. (ed.), "Special TSS-1 Issue," Il Nuovo Cimento, Vol. 17c, January-February, 1994.
- Donohue, D.J., Neubert, T. and Banks, P.M., "Estimating Radiated Power from a Conducting Tethered Satellite System," Journal of Geophysical Research, Vol. 96, p. 21,245-21,253, December 1, 1991.
- Drell, S. D., Foley, H. M., and Ruderman, M. A., "Drag and Propulsion of Large Satellites in the Ionosphere: An Alfvén Propulsion Engine in Space," Journal of Geophysical Research, Vol. 70, No. 13, p. 3131-3145, July 1965.
- Ebner, S. G., "Deployment Dynamics of Rotating Cable-Connected Space Stations," Journal of Spacecraft and Rockets, Vol. 7, No. 10, p. 1274-1275, 1970.
- Estes, R. D., "Alfvén Waves from an Electrodynamical Tethered Satellite System," Journal of Geophysical Research, Vol. 93, A2, p. 945, 1988.
- Fleurisson, E J., VonFlotow, Andreas H. and Pines, Darryll J., "Trajectory Design, and Feedback Stabilization of Tethered Spacecraft Retrieval," Journal of Guidance, Control and Dynamics, Vol. 16, No. 1, p. 160-167, January-February 1993.
- Fujii, H., Uchiyama, K. and Kokubun, K., "Mission Function Control of Tethered Subsatellite Deployment/Retrieval - In-Plane and Out-of-Plane Motion," Journal of Guidance, Control and Dynamics, Vol. 14, p. 471-473, March-April 1991.
- Fujii, H., Kokubun, K., Uchiyama, K. and Suganuma, T., "Deployment/Retrieval Control of a Tethered Subsatellite Under Aerodynamic Effect of Atmosphere," Journal of the Astronautical Sciences, Vol. 40, No. 2, p. 171-188, April-June 1992.
- Fujii, H. A. and Anazawa, S., "Deployment/Retrieval Control of Tethered Subsatellite Through an Optimal Path," Journal of Guidance, Control and Dynamics, Vol. 17, No. 6, p. 1292-1298, December 1994.
- Furta, S.D., "On the Instability of 'Folded' Equilibria of a Flexible Nonstretchable Thread Attached to the Satellite in a Circular Orbit," Celestial Mechanics and Dynamical Astronomy, Vol. 53, No. 3, p. 255-266, 1992.
- Gioulekas, A. and Hastings, D.E., "Role of Current Driven Instabilities in the Operation of Plasma Contactors Used with Electrodynamical Tethers," Journal of Propulsion and Power, Vol. 6, p. 559-566, September-October 1990.
- Glickman, R. E. and Rybak, S. C., "Gravity Gradient Enhancement During Tethered Payload Retrieval," Journal of the Astronautical Sciences, Vol. 35, No. 1, p. 57-74, January-March, 1987.
- Grassi, M. and Cosmo, M. L., "Attitude Dynamics of the Small Expendable-Tether Deployment System," Acta Astronautica, Vol. 36, No. 3, p. 141-148, August 1995.
- Grassi, M. and Cosmo, M. L., "Atmospheric Research with the Small Expendable Deployer System: Preliminary Analysis," Journal of Spacecraft and Rockets, Vol. 33, No. 1, p. 70-78, January-February 1996.
- Greene, M., Rupp, C. C., Walls, J., Wheelock, D. and Lorenzoni, A., "Feasibility Assessment of the Get-Away Tether Experiment," Journal of the Astronautical Sciences, Vol. 35, No. 1, p. 75-96, January-March, 1987.

- Greene, M. E. and Denney, T. S., "On State Estimation for an Orbiting Single Tether System," IEEE Transactions on Aerospace and Electronic Systems, Vol. 27, p. 689-695, July 1991.
- Greene, M. E. and Denney, T. S., Jr., "Real-Time Estimator for Control of an Orbiting Single Tether System," IEEE Transactions on Aerospace and Electronic Systems, Vol. 27, p. 880-883, November 1991.
- Greene, M.E., Carter, J.T. and Walls, J.L., "Linear Adaptive Control of a Single-Tether System," International Journal of Adaptive Control and Signal Processing, Vol. 6, No. 1, p. 1-17, January 1992.
- Grossi, M. D., "A ULF Dipole Antenna on a Spaceborne Platform of the PPEPL Class," Report for NASA contract NAS8-28203, May, 1973.
- Grossi, M. D., "Spaceborne Long Vertical Wire as a Self-Powered ULF/ELF Radiator," IEEE Journal of Oceanic Engineering, Vol. OE-9, No. 3, p. 211-213, July 1984.
- Gullahorn, G., Fuligni, F., Grossi, M. D., "Gravity Gradiometry from the Tethered Satellite System," IEEE Transportation Geoscience Remote Sensing, Vol. GE 23, p. 531-540, 1985.
- Gwaltney, D. A. and Greene, M. E., "Ground-Based Implementation and Verification of Control Laws for Tethered Satellites," Journal of Guidance, Control and Dynamics, Vol. 15, p. 271-273, January-February 1992.
- He, X. and Powell, J. D., "Tether Damping in Space," Journal of Guidance, Control and Dynamics, Vol. 13, p. 104-112, January-February 1990.
- Humble, R. W., "Two Dimensional Tethered Satellite Attitude Dynamics," Journal of the Astronautical Sciences, Vol. 38, p. 21-27, January-March 1990.
- Hurlbut, F.C. and Potter, J.L., "Tethered Aerothermodynamic Research Needs," Journal of Spacecraft and Rockets, Vol. 28, p. 50-57, January-February 1991.
- Ionasescu, R., and Penzo, P. A., "Space Tethers," British Interplanetary Society, Spaceflight, Vol. 30, No. 5, May 1988.
- Isaacs, J. D., Vine, A. C., Bradner, H., and Bachus, G. E., "Satellite Elongation into a True 'Sky-Hook'," Science, Vol. 151, p. 682, 683 (Feb. 1966), Vol. 152, p. 800, Vol. 158, p. 946, 947, Nov. 1967.
- James, H.G., "Wave Results from OEDIPUS A (Rocket Sounding of Plasma Dynamics in Auroral Ionosphere)," Advances in Space Research, Vol. 13, No. 10, p. 5-13, October 1993.
- Kalaghan, P., Arnold, D. A., Colombo, G., Grossi, M., Kirschner, L. R., and Orringer, O., "Study of the Dynamics of a Tethered Satellite System (Skyhook)," NASA Contract NAS8-32199, SAO Final Report, Mar. 1978.
- Kane, T. R., "A New Method for the Retrieval of the Shuttle-Based Tethered Satellite," Journal of the Astronautical Sciences, Vol. 32, No. 3, p. 351-354, July-Sept. 1984.
- Kane, T. R., and Levinson, D. A., "Deployment of a Cable-Supported Payload from an Orbiting Spacecraft," Journal of Spacecraft and Rockets, Vol. 14, No. 7, p. 409-413, 1977.
- Katz, I., Lilley, J.R. Jr., Greb, A., McCoy, J.E., Galofaro, J. and Ferguson, D.C., "Plasma Turbulence Enhanced Current Collection - Results from the Plasma Motor Generator Electrodynamics Tether Flight," Journal of Geophysical Research, Vol. 100, No. A2, February 1995.
- Kelly, W. D., "Delivery and Disposal of a Space Shuttle External Tank to Low-Earth Orbit," Journal of the Astronautical Sciences, Vol. 32, No. 3, p. 343-350, July-Sept. 1984.
- Kerr, W. C., and Abel, J. M., "Traverse Vibrations of a Rotational Counterweighted Cable of Small Flexural Rigidity," AIAA Journal, Vol. 9, No. 12, p. 2326-2332, 1971.
- Keshmiri, M., Misra, A.K. and Modi, V.J., "General Formulation for N-Body Tethered Satellite System Dynamics," Journal of Guidance, Control and Dynamics, Vol. 19, No. 1, p. 75-83, February 1996.
- Kim, E. and Vadali, S. R., "Modeling Issues Related to Retrieval of Flexible Tethered Satellite System," Journal of Guidance, Control and Dynamics, Vol. 18, No. 5, p. 1169-1176, October 1995.
- Kline-Schoder, R. J. and Powell, J.D., "Precision Attitude Control for Tethered Satellites," Journal of Guidance, Control and Dynamics, Vol. 16, No. 1, p. 168-174, January-February 1993.
- Kumar, K., Kumar, R. and Misra, A.K., "Effects of Deployment Rates and Librations on Tethered Payload Raising," Journal of Guidance, Control and Dynamics, Vol. 15, No. 5, p. 1230-1235, September-October 1992.
- Kumar, K., "Geosynchronous Satellites at Sub-Synchronous Altitudes," Acta Astronautica, Vol. 29, No. 3, p. 149-151, March 1993.
- Kyroudis, G. A., and Conway, B. A., "Advantages of Using an Elliptically-Orbiting Tethered-Dumbbell System for a Satellite Transfer to Geosynchronous Orbit," submitted to Journal of Guidance, Control and Dynamics, 1987.

- Lemke, E. H., "On a Lunar Space Elevator," Acta Astronautica, Vol. 12, No. 6, 1985.
- Lemke, L. G., Powell, J. D., He, X., "Attitude Control of Tethered Spacecraft," Journal of the Astronautical Sciences, Vol. 35, No. 1, p. 41-56, January-March, 1987.
- Levin, E. M., "Stability of the Stationary Motions of an Electromagnetic Tether System in Orbit," ISSN 0010-9525, Cosmic Research, Jan. 1988.
- Levin, E. M., "Stability of the Time-Independent Tethered Motions of Two Bodies in Orbit Under the Action of Gravitational and Aerodynamic Forces," Translated from Komicheskie Issledovaniya, Vol. 22, No. 5, p. 675-682, Sept.-Oct. 1984.
- Levin, E.M., "Nonlinear Oscillations of Space Tethers," Acta Astronautica, Vol. 32, No. 5, p. 405-408, May 1994.
- Levin, E.M., "Nearly-Uniform Deployment Strategy for Space Tether Systems," Acta Astronautica, Vol. 32, No. 5, p. 399-403, May 1994.
- Li, Z. and Bainum, P. M., "On the Development of Control Laws for an Orbiting Tethered Antenna/Reflector System Test Scale Model," Journal of Intelligent Material Systems and Structures, Vol. 4, No. 3, p. 343-353, July 1993.
- Liaw, D. and Abed, E., H., "Stabilization of Tethered Satellites During Station Keeping," IEEE Transactions on Automatic Control, Vol. 35, p. 1186-1196, November 1990.
- Lips, K. W. and Modi, V. J., "General Dynamics of a Large Class of Flexible Satellite Systems," Acta Astronautica, Vol. 7, p. 1349-1360, 1980.
- Lips, K. W., Modi, V. J., "Transient Attitude Dynamics of Satellites with Deploying Flexible Appendages," Acta Astronautica, Vol. 5, p. 797-815, Oct. 1978.
- Longuski, J.M., Puig-Suari, J., and Mechals, J., "Aerobraking Tethers for the Exploration of the Solar System," Acta Astronautica, Vol. 35, No. 2/3, pp. 205-214, 1995.
- Longuski, J.M., Puig-Suari, J., Tsiotras, P., and Tragesser, S., "Optimal Mass for Aerobraking Tethers," Acta Astronautica, Vol. 35, No. 8, pp. 489-500, 1995.
- Lorenzini, E. C., "A Three-Mass Tethered System for Micro-g/Variable-g Applications," Journal of Guidance, Control, and Dynamics, Vol. 10, No. 3, May-June 1987. Also in the Russian Journal of Aeronautics/Space Technology, No. 12, Dec. 1987.
- Lorenzini, E. C., Cosmo, M., Vertrella, S., and Moccia, A., "Dynamics and Control of the Tether Elevator/Crawler System," to appear in the Journal of Guidance, Control and Dynamics, 1988.
- Lorenzini, E.C., MD, Grossi, and M. Cosmo, "Low Altitude Tethered Mars Probe," Acta Astronautica, Vol 21, No.1, 1990, pp. 1-12.
- Lorenzini, E. C., Gullahorn, G. E., and Fuligni, F., "Recent Developments in Gravity Gradiometry from the Space-Shuttle-Borne Tethered Satellite System," Journal of Applied Physics, Vol. 63, No. 1, p. 216-223, Jan. 1988.
- Lorenzini, E. C., "Novel Tether-Connected Two-Dimensional Structures for Low Earth Orbits," Journal of Astronautical Sciences, Vol. 36, No. 4, Oct.-Dec. 1988.
- Lorenzini, E.C., Sullivan, J. D. and Post, R. S., "New Techniques for Collecting Data Around the Space Station," Journal of the Astronautical Sciences, Vol. 38, p. 121-141, April-June 1990.
- Lorenzini, E.C., Bortolami, S.B., Rupp, C.C., Angrilli, F., "Control and Flight Performance of Tethered Satellite Small Expendable Deployment System-II," Journal of Guidance, Control, and Dynamics, Vol. 19, No.5, p. 1148-1156, September-October 1996.
- Lüttgen, A. and Neubauer, F.M., "Generation of Plasma Waves by a Tethered Satellite Elongated in the Direction of Flight for Arbitrary Oblique Geometry," Journal of Geophysical Research, Vol. 99, A12, p. 23,349, 1994.
- Maierov, V. A., Popov, V. I., Yanov, I. O., "Analysis of the Dynamics of a System Using Gravitational-Gradient and Gyroscopic Principles of Stabilization," Cosmic Research, Vol. 18, No. 4, p. 348-356, Jul.-Aug. 1980.
- Manaziruddin, and Singh, R.B., "Effects of Small External Forces on the Planar Oscillation of a Cable Connected Satellites System," Celestial Mechanics and Dynamical Astronomy, Vol. 53, No. 3, p. 219-226, 1992.
- Martinez-Sanchez, M., Hastings, D. E., "A Systems Study of a 100 KW Electrodynamic Tether," Journal of the Astronautical Sciences, Vol. 35, No. 1, p. 75-96, January-March, 1987.
- Martinez-Sanchez, M., and Gavit, S., "Orbit Modifications Using Forced Tether Length Variations," Journal of Guidance, Control and Dynamics, Vol. 10, No. 3, p. 233-241, 1987.

- McComas, D. J., Spence, H. E., Karl, R. R., Horak, H. G., Wilkerson, T. D., "Bistatic LIDAR Experiment Proposed for the Shuttle/Tethered Satellite System Missions," Review of Scientific Instruments, Vol. 56, No. 5, p. 670-673, May 1985.
- Misra, A. K., and Modi, V. J., "Deployment and Retrieval of Shuttle Supported Tethered Satellites," Journal of Guidance, Control and Dynamics, Vol. 5, No. 3, p. 278-285, 1982.
- Misra, A. K., Modi, V. J., "The Influence of Satellite Flexibility on Orbital Motion," Celestial Mechanics, Vol. 17, p. 145-165, Feb. 1978.
- Moccia, A. and Vetrella, S., "A Tethered Interferometric Synthetic Aperture Radar (SAR) for a Topographic Mission," IEEE Transactions on Geoscience and Remote Sensing, Vol. 30, p. 103-109, January 1992.
- Moccia, A., Vetrella, S. and Grassi, M., "Attitude Dynamics and Control of a Vertical Interferometric Radar Tethered Altimeter," Journal of Guidance, Control and Dynamics, Vol. 16, No. 2, p. 264-269, March-April 1993.
- Modi, V. J., Chang-fu, G., and Misra, A. K., "Effects of Damping on the Control Dynamics of the Space Shuttle Based Tether System," Journal of the Astronautical Sciences, Vol. 31, No. 1, p. 135-149, Jan.-Mar. 1983.
- Modi, V. J., and Misra, A. K., "On the Deployment Dynamics of Tether Connected Two-Body Systems," Acta Astronautica, Vol. 6, No. 9, p. 1183-1197, 1979.
- Modi, V. J., and Misra, A. K., "Orbital Perturbations of Tethered Satellite Systems," Journal of the Astronautical Sciences, Vol. 25, No. 3, p. 271-278, July-Sept. 1977.
- Modi, V.J., Chang-Fu, G., Misra, A. K., and Xu, D. M., "On the Control of the Space Shuttle Based Tether System," Acta Astronautica, Vol. 9, No. 6-7, p. 437-443, 1982.
- Modi, V.J., Lakshmanan, P.K. and Misra, A.K., "On the Control of Tethered Satellite Systems," Acta Astronautica, Vol. 26, No. 6, p. 411-423, June 1992.
- Modi, V.J., Bachmann, S. and Misra, A.K., "Dynamics and Control of a Space Station Based Tethered Elevator System," Acta Astronautica, Vol. 29, No. 6, p. 429-449, June 1993.
- Moravec, H., "A Non-Synchronous Orbital Skyhook," Journal of the Astronautical Sciences, Vol. 25, No. 4, p. 307-322, Oct.-Dec. 1977.
- Myers, N.B., Ernstmeyer, J., McGill, P., Fraser-Smith, A.C., Raitt, W.J. and Thompson, D.C., "Ground-Based VLF Measurements During Pulsed Electron Beam Emissions in the Ionosphere," Advances in Space Research, Vol. 13, No. 10, p. 99-102, October 1993.
- Netzer, E. and Kane, T. R., "An Alternate Approach to Space Missions Involving a Long Tether," Journal of the Astronautical Sciences, Vol. 40, No. 3, p. 313-327, July-September 1992.
- Netzer, E. and Kane, T. R., "Deployment and Retrieval Optimization of a Tethered Satellite System," Journal of Guidance, Control and Dynamics, Vol. 16, No. 6, p. 1085-1091, November-December 1993.
- Netzer, E. and Kane, T., "Estimation and Control of Tethered Satellite Systems," Journal of Guidance, Control and Dynamics, Vol. 18, No. 4, p. 851-858, August 1995.
- Neubert T., Gilchrist, B. and Ungstrup, E., "AMPAS - A New Active Experiment Mission (Active Magnetospheric Particle Acceleration Satellite)," Advances in Space Research, Vol. 15, No. 12, p. 3-12, June 1995.
- Nixon, D. D., "Dynamics of a Spinning Space Station with a Counterweight Connected by Multiple Cables," Journal of Spacecraft and Rockets, Vol. 9, No. 12, p. 896-902, 1972.
- Oberhardt, M.R., Hardy, D.A., Thompson, D.C., Raitt, W.J., Melchioni, E., Bonifazi, C. and Gough, M.P., "Positive Spacecraft Charging as Measured by the Shuttle Potential and Return Electron Experiment," IEEE Transactions on Nuclear Science, Vol. 40, No. 6, p. 1532-1541, December 1993.
- Pasca M. and E. C. Lorenzini, "Optimization of a Low Altitude Tethered Probe for Martian Atmospheric Collection", The Journal of the Astronautical Sciences, Vol. 44, No.2, 1996, pp.191-205
- Pasca, M. Pignataro, M. and Luongo, A., "Three-Dimensional Vibrations of Tethered Satellite System," Journal of Guidance, Control and Dynamics, Vol. 14, p. 312-320, March-April 1991.
- Pearson, J., "Anchored Lunar Satellites for Cislunar Transportation and Communication," Journal of the Astronautical Sciences, Vol. 27, No. 1, Jan.-Mar. 1979.
- Pearson, J., "The Orbital Tower: A Spacecraft Launcher Using the Earth's Rotational Energy," Acta Astronautica, Vol. 2, No. 9/10, p. 785-799, Sept.-Oct. 1975.
- Pelaez, J., "On the Dynamics of the Deployment of a Tether from an Orbiter. I - Basic Equations," Acta Astronautica, Vol. 36, No. 2, p. 113-122, 1995.
- Pelaez, J., "On the Dynamics of the Deployment of a Tether from an Orbiter. II - Exponential Deployment," Acta Astronautica, Vol. 36, No. 6, p. 313-335, 1995.

- Pengelley, C. D., "Preliminary Survey of Dynamic Stability of Cable-Connected Spinning Space Station," Journal of Spacecraft and Rockets, Vol. 3, No. 10, p. 1456-1462, Oct. 1966.
- Penzo, P. A., and Mayer, H. L., "Tethers and Asteroids for Artificial Gravity Assist in the Solar System," Journal of Spacecraft and Rockets, Vol. 23, No. 1, Jan.-Feb. 1986.
- Pines, D.J., VonFlotow, A.H. and Redding, D.C., "Two Nonlinear Control Approaches for Retrieval of a Thrusting Tethered Subsatellite," Journal of Guidance, Control and Dynamics, Vol. 13, p. 651-658, July-August 1990.
- Polites, M.E., "Reconstructing Tethered Satellite Skiprope Motion by Bandpass Filtering Magnetometer Measurements," Journal of Dynamic Systems, Measurement and Control, Vol. 114, No. 3, p. 481-485, September 1992.
- Pradhan, S., Modi, V. J. and Misra, A. K., "On the Inverse Control of the Tethered Satellite System," Journal of the Astronautical Sciences, Vol. 43, No. 2, p. 179-193, June 1995.
- Pringle, R., "Exploration of Nonlinear Resonance in Damping an Elastic Dumb-Bell Satellite," AIAA Journal, No. 7, p. 1217-1222, 1968.
- Puig-Suari, J., Logunski, J. M. and Tragesser, S. G., "Aerocapture with a Flexible Tether," Journal of Guidance, Control and Dynamics, Vol. 18, No. 6, p. 1305-1312, December 1995.
- Puig-Suari, J., Logunski, J. M. and Tragesser, S. G., "A Tether Sling for Lunar and Interplanetary Exploration," Acta Astronautica, Vol. 36, No. 6, p. 291-295, September 1995.
- Quadrelli, B.M. and Lorenzini, E.C., "Dynamics and Stability of a Tethered Centrifuge in Low Earth Orbit," Journal of the Astronautical Sciences, Vol. 40, p. 3-25, January-March 1992.
- Raitt, W.J., Ernstmeyer, James, Myers, Neil B., White, A.B., Sasaki, Susumu, Oyama, Koh-ichiro, Kawashima, Nobuki, Fraser-Smith, Anthony C., Gilchrist, Brian E. and Hallinan, Thomas J., "VLF Wave Experiments in Space Using a Modulated Electron Beam," Journal of Spacecraft and Rockets, Vol. 32, No. 4, p. 670-679, August 1995.
- Ross, J., "Super-strength Fiber Applications," Astronautics and Aeronautics, Dec. 1977.
- Rupp, C. C., and Laue, J. H., "Shuttle/Tethered Satellite System," The Journal of the Astronautical Sciences, Vol. 26, No. 1, p. 1-17, Jan. 1978.
- Rupp, C. C., et al, "Shuttle/Tethered Satellite System Conceptual Design Study," NASA TMX-73365, MSFC, Alabama, Dec. 1976.
- Samanta R., R.I. and Hastings, D.E., "Theory of Plasma Contactor Neutral Gas Emissions for Electrodynamic Tethers," Journal of Spacecraft and Rockets, Vol. 29, No. 3, p. 405-414, May-June 1992.
- Sanmartin, J.R. and Lam, S.H., "Far-Wake Structure in Rarefield Plasma Flows Past Charged Bodies," Phys. Fluids, 14, p. 62, 1971.
- Sanmartin, J.R., Martinez-Sanchez, M. and Ahedo, E., "Bare Wire Anodes for Electrodynamic Tethers," Journal of Propulsion and Power, Vol. 9, No. 3, p. 353-360, May-June 1993.
- Sanmartin, J.R. and Martinez-Sanchez, M., "The Radiation Impedance of Orbiting Conductors," Journal of Geophysical Research, Vol. 100, No. A2, p. 1677-1686, February 1, 1995.
- Santangelo, A. D. and Johnson, G. E., "Optimal Wing Configuration of a Tethered Satellite System in Free Molecular Flow," Journal of Spacecraft and Rockets, Vol. 29, No. 5, p. 668-670, September-October 1992.
- Singh, N. and Vashi, B. I., "Current Collection by a Long Conducting Cylinder in a Flowing Magnetized Plasma," Journal of Spacecraft and Rockets, Vol. 28, p. 592-598, September-October 1991.
- Singh, R. B., "Three Dimensional Motion of a System of Two Cable-Connected Satellites in Orbit," Acta Astronautica, Vol. 18, No. 5, p. 301-308, 1973.
- Stabekis, P., and Bainum, P. M., "Motion and Stability of Rotating Space Station-Cable-Counterweight Configuration," Journal of Spacecraft and Rockets, Vol. 7, No. 8, p. 912-918, 1970.
- Stenzel, R.L. and Urrutia, J.M., "Currents Between Tethered Electrodes in a Magnetized Laboratory Plasma," Journal of Geophysical Research, Vol. 95, p. 6209-6226, May 1, 1990.
- Stuiver, W., and Bainum, P. M., "A Study of Planar Deployment Control and Libration Damping of a Tethered Orbiting Interferometer Satellite," Journal of the Astronautical Sciences, Vol. 20, No. 6, p. 321-346, May-June 1973.
- Stuiver, W., "Dynamics and Configuration Control of a Two-Body Satellite System," Journal of Spacecraft and Rockets, Vol. 11, No. 8, p. 345-346, 1974.
- Sutton, G. W., and Diederich, F. W., "Synchronous Rotation of a Satellite at Less Than Synchronous Altitude," AIAA Journal, Vol. 5, No. 4, p. 813-815, 1967.

Swet, C. J., and Whisnant, J. M., "Deployment of a Tethered Orbiting Interferometer," Journal of the Astronautical Sciences, Vol. 17, No. 1, p. 44-59, July-Aug. 1969.

Tan, Z. and Bainum, P., M., "Optimal Linear Quadratic Gaussian Digital Control of an Orbiting Tethered Antenna/Reflector System," Journal of Guidance, Control and Dynamics, Vol. 17, No. 2, p. 234-241, April 1994.

Tiesenhhausen, G. von, ed., "The Roles of Tethers on Space Station," NASA-TM-86519, NASA/MSFC, Oct. 1985.

Tyc, G., Vigneron, F.R. and Jablonski, A.M., "Two-Body Space Dynamics Technology Demonstration for the Biceps Small Satellite Mission," Canadian Aeronautics and Space Journal, Vol. 40, No. 1, p. 3-9, March 1994.

Tyc, G. and Han, R.P.S., "Attitude Dynamics Investigation of the OEDIPUS-A Tethered Rocket Payload," Journal of Spacecraft and Rockets, Vol. 32, No. 1, p. 133-141, February 1995.

Usui, H., Matsumoto, H. and Omura, Y., "Electron Beam Injection and Associated LHR Wave Excitation - Computer Experiments of Electrodynamic Tether System," Geophysical Research Letters, Vol. 18, p. 821-824, May 1991.

Usui, H., Matsumoto, H. and Omura, Y., "Plasma Response to High Potential Satellite in Electrodynamic Tether System," Journal of Geophysical Research, Vol. 98, No. A2, p. 1531-1544, February 1, 1993.

Vadali, S. R., "Feedback Tether Deployment and Retrieval," Journal of Guidance, Control and Dynamics, Vol. 14, p. 469-470, March-April 1991.

Vadali, S.R. and Kim, E.-S., "Feedback Control of Tethered Satellites Using Lyapunov Stability Theory," Journal of Guidance, Control and Dynamics, Vol. 14, p. 729-735, July-August 1991.

Vadali, S. R. and Kim, E., "Nonlinear Feedback Deployment and Retrieval of Tethered Satellite Systems," Journal of Guidance, Control and Dynamics, Vol. 15, p. 28-24, January-February 1992.

Vannaroni, G., Giovi, R. and DeVenuto, F., "Laboratory Simulation of the Interaction Between A Tethered Satellite System and the Ionosphere," Nuovo Cimento C, Serie 1, Vol. 15C, No. 5, p. 685-701, September-October 1992.

Vom Stein, R. and Neubauer, F.M., "Plasma Wave Field Generation by the Tethered Satellite System," Journal of Geophysical Research, Vol. 97, No. A7, p. 10,849-10,856, July 1, 1992.

von Flotow, A. H., and Williamson, P. R., "Deployment of a Tethered Satellite Pair into Low Earth Orbit for Plasma Diagnostics," The Journal of the Astronautical Sciences, Vol. 21, No. 1, p. 135-149, 1983.

Warnock, T. W. and Cochran, J. E., Jr., "Orbital Lifetime of Tethered Satellites," Journal of the Astronautical Sciences, Vol. 41, No. 2, p. 165-188, April-June 1993.

Wood, G. M., Siemers, P.M., Squires, R. K., Wolf, H. and Carlomagno, G. M., "Downward-Deployed Tethered Platforms for High-Enthalpy Aerothermodynamic Research," Journal of Spacecraft and Rockets, Vol. 27, p. 215-221, March-April 1990.

Wright, A. N. and Schwartz, S. J., "The Equilibrium of a Conducting Body Embedded in a Flowing Plasma," Journal of Geophysical Research, Vol. 95, p. 4027-4038, April 1, 1990.

Yu, S., "On the Dynamics and Control of the Relative Motion Between Two Spacecraft," Acta Astronautica, Vol. 35, No. 6, p. 403-409, March 1995.

Zhu, R., Misra, A.K. and Modi, V.J., "Dynamics and Control of Coupled Orbital Motion of Tethered Satellite Systems," Journal of the Astronautical Sciences, Vol. 42, No. 3, p. 319-342, September 1994.

SECTION 8.0 CONTACTS

A -

Dr. Eduardo Ahedo
E.T.S.I. Aeronauticos
Plaza Cardenal Cisneros 3
28040 Madrid, SPAIN
3413366310

Mr. A.J. Alfonzo
Omitron, Inc.
6411 Ivy Lane
Suite 600
Greenbelt, MD 20770
301/474-1700

Mr. Andrew M. Allen
NASA, Johnson Space Center (CB)
Houston, TX 77058
713/244-8719

Prof. Yakov Alpert
Harvard Smithsonian Center
for Astrophysics
60 Garden Street
Cambridge, MA 02138
617/495-7933

Dr. Jesus Pelaez Alvarez
E.T.S.I. Aeronauticos
Dpto. Fisica Aplicada
Pl. Cardenal Cisneros 3
28040, Madrid, SPAIN
3413366306

Mr. John Anderson
NASA Headquarters
Mail Code CC
Washington, DC 20546
202/358-4665

Prof. Francesco Angrilli
CISAS - University of Padova
Dept. of Mechanical Engineering
VIA Venezia, 1
35131, Padova, ITALY
39498286790

Mr. David A. Arnold
75 Woodbine Road
Belmont, MA 02178
617/484-7741

B -

Prof. Peter M. Bainum
Howard University
Dept. of Mechanical Engineering
2300 6th Street, N.W.
Washington, DC 20059
202/806-6612

Prof. Keith G. Balmain
University of Toronto
Dept. of Electrical and
Computer Engineering
10 King's College Road
Toronto, Ontario, M5S 1A4 CANADA
416/978-3127

Mr. Ivan Bekey
NASA Headquarters
Advanced Concepts Office
Washington, DC 20546

Mr. Douglas Bentley
Cortland Cable Company
177 Port Watson Street
Cortland, NY 13045
607/753-8303

Prof. Silvio Bergamaschi
Padova University
Dept. of Mechanical Engineering
VIA Venezia 1
35131 Padova, ITALY
39498286809

Prof. Franco Bernelli-Zazzera
Politecnico di Ingegneria Aerospaziale
Politecnico di Milano
Via Golgi 40
20133 Milano, ITALY
39223994000

Dr. Thomas G. Berry
University of Manitoba
Dept. of Applied Mathematics
Winnipeg, Manitoba, R3T 2N2 CANADA
204/474-8345

Mr. Franco Bevilacqua
Alenia Spazio S.p.A. - Turin Plant
Advanced Studies Department
Corso Marche, 41
10146 Torino, ITALY
39117180718

Prof. Gianandrea Bianchini
University of Padova
Dept. of Mechanical Engineering
VIA Venezia 1
35131, Padova, ITALY
39498286808

Dr. Haik Biglari
Sverdrup Technology, Inc.
620 Discovery Drive
Huntsville, AL 35806
205/544-6890

Mr. Sven G. Bilén
University of Michigan
Space Physics Research Laboratory
2455 Hayward Street
Ann Arbor, MI 48109-2143
313/764-8461

Mr. Christopher Blunk
Eleanor Roosevelt High School
C/O W.J. Webster, Jr.
NASA, Goddard Space Flight Center
Code 920.2
Greenbelt, MD 20771
301/286-4506

Dr. Carlo Bonifazi
Agenzia Spaziale Italiana
Viale Regina Margherita 202
00198 Roma, ITALY

Mr. Brian Briswell
Arizona State University
Dept. of Mechanical
and Aerospace Engineering
Box 876106
Tempe, AZ 85287-6106
602/965-4363

Mr. Richard Brooke
12009 Lake Newport Road
Herndon, VA 22070

Mr. Larry L. Burgess
Lockheed Martin Astronautics
#3 Red Fox Lane
Littleton, CO 80127-5710
303/971-7521

Dr. William J. Burke
Phillips Laboratory/GPSG
29 Randolph Road
Hanscom AFB, MA 01731-3010
617/377-3980

C -

Mr. Michael A. Calabrese
NASA Headquarters
Code SS
300 E Street, S.W.
Washington, DC 20546
202/358-0899

Prof. Giovanni Carlomagno
Dip. di Energetica, Termofluidodinamica
Applicata e
Condizionamento Ambientale
Universita' di Napoli
P.le Tecchio, 80
80125 Napoli
39-81-7682178

Prof. Robert L. Carovillano
NASA Headquarters
Code SS
300 E. Street, S.W.
Washington, DC 20546
202/358-0894

Mr. Joseph A. Carroll
Tether Applications
1813 Gotham Street
Chula Vista, CA 91913-2624
619/421-2100

Dr. Kelly Chance
Harvard-Smithsonian Center
for Astrophysics
60 Garden Street
MS 50
Cambridge, MA 02138
617/495-7389

Mr. Chia-Lie Chang
Science Applications International Corp.
1710 Goodridge Drive, T-2-3
McLean, VA 22102
703/734-5588

Dr. Franklin R. Chang-Diaz
NASA, Johnson Space Center
Houston, TX 77058
713/244-8923

Mr. Maurizio Cheli
NASA, Johnson Space Center
Houston, TX 77058
713/244-8739

Mr. Aaron Chilbert
Naval Research Laboratory
Code 8210
4555 Overlook Avenue, S.W.
Washington, DC 20375-5000

Dr. Palmer B. Chiu
NASA, Johnson Space Center
Automation, Robotics,
and Simulation Division
NASA Road One; Mail Code ER6
Houston, TX 77058
713/483-8139

Dr. Dean Chlouber
System Planning Corporation
18100 Upper Bay Road, Suite 208
Houston, TX 77058
713/333-2666

Dr. Paul J. Coleman, Jr.
UCLA - IGPP
Inst of Geophysics & Planetary Physics
405 Hilgard Avenue
Los Angeles, CA 90095-1776
310/825-1776

Dr. Luis Conde
E.T.S.I. Aeronauticos
Dept. Fisica Aplicada
Pl. Cardenal Cisneros, 3
28040 Madrid, SPAIN
3413366305

Ms. Carolynn Conley
Muniz Engineering
P.O. Box 591672
Houston, TX 77259-1672
713/244-8150

Dr. David Cooke
Phillips Laboratory
PL/WSCF
Hanscom AFB, MA 01731-3010
617/377-2931

Dr. Mario L. Cosmo
Harvard-Smithsonian Center
for Astrophysics
60 Garden Street, MS 80
Cambridge, MA 02138
617/495-7412

Mr. Donald S. Crouch
Lockheed Martin
Mail Stop S8071
P.O. Box 179
Denver, CO 80201
303/977-3408

Mr. Kenneth H. Crumbly
3418 News Road
Williamsburg, VA 23188
757/258-5422

D -

Dr. Roberto Da Forno
CISAS - University of Padova
Via Venezia 1
35131 Padova, ITALY
39498286801

Mr. Mark A. Davis
7515 Mission Drive
Lanham, MD 20706
301/805-3960

Dr. Anthony DeCou
Northern Arizona University
College of Engineering
Box 5600
Flagstaff, AZ 86011
520/523-6114

Dr. Adarsh Deepak
Science and Technology Corporation
101 Research Drive
Hampton, VA 23666-1340
757/865-1894

Mr. John K. Diamond
NASA, Langley Research Center
M/S 471
Hampton, VA 23681-0001
757/864-1668

Prof. Luigi de Luca
Dip. di Energetica, Termofluidodinamica
Applicata e
Condizionamento Ambientale
Universita' di Napoli
P.le Tecchio, 80
80125 Napoli
39-81-7682182

Dr. Donald J. Dichmann
University of Maryland
Insitute for Physical Sciences
and Technology (IPST)
College Park, MD 20742
301/405-7887

Mr. Marino Dobrowolny
Istituto di Fisica dello Spazio
Interplanetario, CNR
00044 Frascati, ITALY
3969421017

Dr. Denis J. Donohue
Applied Physics Laboratory
Johns Hopkins University
Johns Hopkins Road
Laurel, MD 20723-6099
301/953-6258

Mr. Jean-Jacques Dordain
European Space Agency
8- 10 Rue Mario Nikis
75738 Paris Cedex 15, FRANCE
33153697338

Mrs. Patricia M. Doty
NASA, Marshall Space Flight Center
Mail Code FA64
Marshall Space Flight Center, AL 35812
205/544-4136

Mr. Michael Douglass
University of N Carolina - Chapel Hill
c/o W. J. Webster, Jr.
NASA/GSFC
Code 920.2
Greenbelt, MD 20771
301/286-4506

Dr. Adam T. Drobot
Science Applications International Corp.
1710 Goodridge Drive, T-2-3
McLean, VA 22102
703/734-5595

E -

Mr. Walter Eliuk
Bristol Aerospace Limited
660 Berry Street
P.O. Box 874
Winnipeg, Manitoba, R3C 2S4 CANADA
204/775-8331

Mr. Raymond A. Ernst
Lockheed Martin Astronautics
1725 Jefferson Davis Highway
Suite 300
Arlington, VA 22202
703/413-5762

Mr. Jay N. Estes
NASA, Johnson Space Center
Mail Code EG2
2101 NASA Road One
Houston, TX 77058
713/483-8379

Dr. Robert D. Estes
Harvard-Smithsonian Center
for Astrophysics
60 Garden Street
Cambridge, MA 02138
617/495-7261

Dr. Steven W. Evans
NASA, Marshall Space Flight Center
Building 4203, Mail Stop EL58
Marshall Space Flight Center, AL 35812
205/544-8072

F -

Dr. Dale C. Ferguson
NASA, Lewis Research Center
Mail Stop 302-1
21000 Brookpark Road
Cleveland, OH 44135
216/433-2298

Mr. Enectali Figueroa
University of Puerto Rico
P.O. Box 5088 College Station
Mayaguez, 00681 PUERTO RICO
809/265-4846

Mr. Howard A. Flanders
Lockheed Martin Astronautics
Mail Stop S8071
P.O. Box 179
Denver, CO 80201
303/977-3669

Dr. Robert L. Forward
Tethers Unlimited
8114 Pebble Court
Clinton, WA 98236
360/579-1340

G -

Mr. Stephen Gates
Naval Research Laboratory
4555 Overlook Avenue, S.W.,
Code 8231
Washington, DC 20375
202/767-7680

Ms. Louise C. Gentile
Phillips Laboratory / GPSG
29 Randolph Road
Hanscom AFB, MA 01731-3010
617/377-7002

Dr. Sig Gerstl
Los Alamos National Lab
NIS/LDRD, MS-F658
Los Alamos, NM 87545
505/667-0952

Dr. Francesco Giani
Alenia Spazio S.p.A.
c. Marche 41
10146 Torino, ITALY
39117180716

Prof. Brian E. Gilchrist
University of Michigan
Space Physics Research Laboratory
2455 Hayward
Ann Arbor, MI 48109-2143
313/763-6230

Dr. John R. Glaese
Control Dynamics
Division of bd Systems
600 Boulevard South, Suite 304
Huntsville, AL 35803
205/882-2720

Mr. Howard Goldstein
NASA, Ames Research Center
Building 229-3
Moffett Field, CA 94030
415/604-6103

Dr. Michael A. Greenfield
HASA Headquarters
Office of Safety and Mission Assurance
300 E Street, S.W.
Washington, DC 20546
202/358-1930

Dr. Mario D. Grossi
Harvard-Smithsonian Center
for Astrophysics
60 Garden Street
MS 80
Cambridge, MA 02138
617/495-7196

Dr. Umberto Guidoni
Italian Space Agency (ASI)
C/O NASA Johnson Space Center
Houston, TX 77058
713/244-2230

Dr. Gordon Gullahorn
Harvard-Smithsonian Ctr for Astrophysics
M/S 80
60 Garden Street
Cambridge, MA 02138
617/495-7419

H -

Ms. Linda Habash
University of Michigan
Space Physics Research Lab
2455 Hayward
Ann Arbor, MI 48109-2141
313/764-8461

Prof. Dr. -Ing W. Hallmann
Fachhochschule Aachen
Space Department
Hohenstaufenallee 6
D-52064 Aachen, GERMANY
24160092362

Prof. Ray P.S. Han
University of Manitoba
Dept. of Mechanical
and Industrial Engineering
Winnipeg, Manitoba, R3T 2N2 CANADA
204/474-9519

Dr. David A. Hardy
Phillips Laboratory/GPSG
29 Randolph Road
Hanscom AFB, MA 01731-3010

Mr. James Harrison
NASA, Marshall Space Flight Center
Mail Code FA34
Huntsville, AL 35812
205/544-0629

Mr. Steven L. Hast
The Aerospace Corporation
P.O. Box 92957 M4/946
Los Angeles, CA 90009-2957
310/336-8968

Prof. Daniel E. Hastings
Massachusetts Institute of Technology
33-207 Department of Aero/Astro
77 Massachusetts Avenue
Cambridge, MA 02139
617/253-0906

Mr. Kazuo Ben Hayashida
NASA, Marshall Space Flight Center
ED52
Marshall Space Flight Center, AL 35812
205/544-4308

Prof. Roderick A. Heelis
Center for Space Sciences
Mail Stop: FO22
The University of Texas at Dallas
Box 830688
2601 N. Floyd Road
Richardson, TX 75080
214/883-2822

Mr. S. Herbinier
CNES
18 avenue Edouard Belin
31055 Toulouse Cedex, FRANCE
3361273439

MAJ Richard Higgins, Jr.
SMC/IMO
2420 Vela Way
Suite 1467-A5
Los Angeles AFB, CA 90245-4659
310/416-7651

Dr. J.M. Hinds
Space Telescope Science Institute
3700 San Martin Drive
Baltimore, MD 21218
410/338-4489

Dr. Noel W. Hinners
Lockheed Martin Astronautics
Mail Stop S-8000
P.O. Box 179
Denver, CO 80201
303/971-1581

Dr. Jeffrey A. Hoffman
NASA, Johnson Space Center
Mail Code CB
Houston, TX 77058
713/244-8723

Dr. John H. Hoffman
University of Texas at Dallas
2601 North Floyd Road
Richardson, TX 75080
214/883-2840

Dr. Toshihisa Honma
Massachusetts Institute of Technology
Dept. of Aeronautics and Astronautics
77 Massachusetts Avenue
Room 9-349
Cambridge, MA 02139-4307
617/258-7357

Mr. George D. Hopson
NASA, Marshall Space Flight Center
Marshall Space Flight Center, AL 35812
205/544-1735

Mr. Scott Horowitz
NASA, Johnson Space Center (CB)
Houston, TX 77058
713/244-8719

Dr. Robert P. Hoyt
Tethers Unlimited
8011 16th Avenue, N.E.
Seattle, WA 98115
206/525-9067

Mr. Brian Humphrey
Eleanor Roosevelt High School
C/O Dr. W.J. Webster, Jr.
NASA Goddard Space Flight Center
C/O 920.2
Greenbelt, MD 20771
301/286-4506

Prof. Franklin C. Hurlbut
University of California at Berkeley
Dept. of Mechanical Engineering
6173 Etcheverry Hall
Berkeley, CA 94720
510/642-7230

I -

Dr. Valerio Iafolla
C.N.R. I.F.S.I.
Via G. Galiles C.P.87
00044 Frascati RM, ITALY
39694186220

Dr. Devrie Intriligator
Carmel Research Center
P.O. Box 1723
Santa Monica, CA 90406
310/453-2983

Dr. George E. Ioup
University of New Orleans
Dept. of Physics
New Orleans, LA 70148
504/286-5591

Dr. Juliette W. Ioup
University of New Orleans
Dept. of Physics
New Orleans, LA 70148
504/286-6715

Mr. J.M. Gavira Izquierdo
ESTEC
YM Division
Keplerlaan 1
2200 AG Noordwijk, THE NETHERLANDS
31171984314

J -

Dr. Alexander M. Jablonski
Canadian Space Agency
DSM
6767 route de l'Aéroport
Saint-Hubert, Quebec, J3Y 8Y9 CANADA
514/926-4686

Dr. H. Gordon James
Communications Research Centre
P.O. Box 11490, Station "H"
Ottawa, Ontario, K2H 8S2 CANADA
613/998-2230

Mr. F.L. Janssens
ESTEC/ESA
Keplerlaan 1
Postbus 299
2200 AG Noordwijk, THE NETHERLANDS
31171983802

Mr. Les Johnson
NASA, Marshall Space Flight Center
Mail Code PS02
Huntsville, AL 35812
205/544-0614

Dr. R. Jerry Jost
System Planning Corporation
Center for Space Physics
18100 Upper Bay Road, Suite 208
Houston, TX 77058
713/333-2666

K -

Dr. Ira Katz
S-Cubed Division of Maxwell Labs
3398 Carmel Mountain Road
San Diego, CA 92121-1095
619/453-0060

Prof. Paul J. Kellogg
University of Minnesota
School of Physics and Astronomy
116 Church Street, S.E.
Minneapolis, MN 55455
612/624-1668

Dr. Vladomir Kim
Research Institute of Applied Mechanics
and Electrodynamics of Moscow
Aviation Institute,
4. Volokolam Snosse, Moscow, 125871,
RUSSIA
951580020

Dr. Kate P. Kirby
Harvard-Smithsonian Center
for Astrophysics
60 Garden Street
MS 14
Cambridge, MA 02138
617/495-7237

Mr. Brian Kirouac
C/O Dr. W.J. Webster, Jr.
NASA, Goddard Space Flight Center
Code 920.2
Greenbelt, MD 20771
301/286-4506

Ms. Sheryl L. Kittredge
NASA, Marshall Space Flight Center
Mail Code ED63
Huntsville, AL 35812
205/544-9032

Mr. Stanislav I. Klimov
Space Research Institute of the
Russian Academy of Sciences
84/32 Profsoyuznaya
Moscow 117810, RUSSIA
70953331100

Mr. Joseph C. Kolecki
NASA, Lewis Research Center
Mail Stop 302-1
21000 Brookpark Road
Cleveland, OH 44135
216/433-2296

Mr. Paul Kolodziej
NASA, Ames Research Center
Mail Stop 234-1
Moffett Field, CA 94035
415/604-0356

Mr. William Kosmann
Interstel, Inc.
8000 Virginia Manor Road
Suite 180
Beltsville, MD 20705
301/210-0012

Mrs. Linda Habash Krause
University of Michigan
Space Research Building
2455 Hayward
Ann Arbor, MI 48109-2143
313/764-8461

Dr. Manfred Krishke
Kayser-Threde GmbH
80337 Munchen, GERMANY
498972495127

Mr. Frank M. Kustas
Lockheed Martin Astronautics
P.O. Box 179
Mail Stop F3085
Denver, CO 80201
303/971-9107

Mr. George Kyroudis
Spectrum Astro, Inc.
1440 N. Fiesta Boulevard
Gilbert, AZ 85234
602/892-8200

L -

Dr. J.G. Laframboise
York University
4700 Keele Street
North York, Ontario, M3J 1P3 CANADA
416/736-5621

Dr. James R. LaFrieda
The Aerospace Corporation
M6/210
P.O. Box 92957
Los Angeles, CA 90009
310/416-7177

Mr. David D. Lang
Lang Associates
2222 70th Avenue, S.E.
Mercer Island, WA 98040
206/236-2579

Dr. Jean-Pierre Lebreton
ESA/ESTEC
Mail Code 50
Keplerlaan 1, 2200 AG Noordwijk,
THE NETHERLANDS
31171983600

Mr. Enzo Letico
ASI Washington Representative
Italian Space Agency
250 E. Street, S.W., Suite 300
Washington, DC 20024
202/863-1298

Mr. George M. Levin
NASA Headquarters
Mail Code MP
300 E Street, S.W.
Washington, DC 20546-0001
202/358-4478

Dr. Yevgeniy M. Levin
University of Minnesota
Dept. of Aerospace Engineering
and Mechanics
107 Akerman Hall
Minneapolis, MN 55455
612/933-3796

Dr. Mark J. Lewis
University of Maryland
Dept. of Aerospace Engineering
College Park, MD 20742-3015
301/405-1133

Dr. Weiwei Li
York University
Dept. of Physics and Astronomy
4700 Keele Street
North York, Ontario, M3J 1P3 CANADA
416/736-2100

Dr. Renato Licata
Alenia Spazio S.p.A. - Turin Plant
Control & Dynamics Department
Corso Marche, 41
10146 Torino, ITALY
39117180233

Dr. Garry M. Lindberg
Canadian Space Agency
6767 Route de L'Aéroport
St-Hubert, Quebec, J3Y 8Y9 CANADA
514/926-4372

Mr. C.R. Lippincott
University of Texas at Dallas
William B. Hanson Center for
Space Sciences
P.O. Box 830688 / M/SF022
Richardson, TX 75083-0688
214/883-2819

Prof. James M. Longuski
School of Aeronautics & Astronautics
Purdue University
1282 Grissom Hall
West Lafayette, IN 47907-1282
317/494-5139

Dr. Enrico Lorenzini
Harvard-Smithsonian Center for Physics
for Astrophysics
60 Garden Street
MS 80
Cambridge, MA 02138
617/495-7211

Dr. Charles A. Lundquist
The University of Alabama
in Huntsville
301 Sparkman Drive
Huntsville, AL 35899
205/895-6620

Dr. Andrea A.E. Luttgen
University of Toronto
Dept. of Elec. & Comp. Engineering
10 King's College Road
Toronto, Ontario, M5S 1A4 CANADA
416/978-5831

M -

Mr. Bruce A. Mackenzie
Draper Laboratory
M/S 22
555 Technology Square
Cambridge, MA 02139
617/258-2828

Mr. Robert J. Mahoney
NASA, Johnson Space Center
Mail Code DT23 / Rendezvous Training
Houston, TX 77058
713/244-7377

Mr. Franco Malerba
Via Contore 10/6
Genova 16149, ITALY
39106450365

Dr. Gianfranco Manarini
Agenzia Spaziale Italiana
Viale Regina Margherita 202
00198 Rome, ITALY
3968567361

Prof. Franco Mariani
Via Ricerca Scientifica 11
00133 Roma, Italy
39678792319

Dr. Hartmut Marschall
Universität Köln
Institut f. Geophysik und Meteorologie
Albertus-Magnus-Platz
Köln 50923, GERMANY
492214703387

Mr. Leland S. Marshall
Lockheed Martin Astronautics
P.O. Box 179
Mail Stop 58071
Denver, CO 80201
205/544-1927

Mr. Patrick Martin
Vitro Corporation
400 Virginia Avenue
Washington, DC
202/646-6371

Mr. Manuel Martinez-Sanchez
Massachusetts Institute of Technology
Dept. of Aeronautics and Astronautics
Cambridge, MA 02139
617/253-5613

Mr. Robert O. McBrayer
NASA, Marshall Space Flight Center
Code JA71
Marshall Space Flight Center, AL 35812
205/544-1926

Dr. James E. McCoy
NASA, Johnson Space Center
Code 5N3
Houston, TX 77058
713/483-5068

Dr. Leonard T. Melfi
Science and Technology Corporation
101 Research Drive
Hampton, VA 23666-1340
757/865-1894

Dr. S.B. Mende
Dept. 91-20, 252
Lockheed
3251 Hanover St.
Palo Alto, CA 94024

Dr. Pietro Merlina
Alenia Spazio S.p.A. - Turin Plant
Advanced Studies Department
Corso Marche, 41
10146 Torino, ITALY
39117180718

Dr. Luca Minna
Advanced Engineering Technology
Corte Lambruschini - Piazza Borgo Pila 40
16129 Genova - ITALY
39105531425

Prof. Arun K. Misra
McGill University
Dept. of Mechanical Engineering
817 Sherbrooke Street West
Montreal, CQ, H3A 2K6 CANADA
415/398-6288

Prof. Antonio Moccia
Dip. di Scienza e Ingegneria dello Spazio,
Univ. di Napoli, P.le Tecchio 80, 80125
Napoli, Italy,
39-81-7682158

Dr. Vinod J. Modi
University of British Columbia
Dept. of Mechanical Engineering
2324 Main Mall
Vancouver, B.C., V6T 1Z4 CANADA
604/822-2914

Mr. Richard Moyer
Advent Systems, Inc.
P.O. Box 222861
Chantilly, VA 22021
703/631-3498

Mr. Ronald M. Muller
NASA, Goddard Space Flight Center
Code 170
Mission to Planet Earth Office
Greenbelt, MD 20771
301/286-9695

Ing. Bruno Musetti
Alenia Spazio S.p.A. - Turin Plant
Control and Dynamics Department
Gruppo Sistemi Spaziali
Corso Marche, 41
10146 Torino, ITALY
39117180752

N -

Mr. Claude Nicollier
NASA, Johnson Space Center
Houston, TX 77058

Ms. Penny L. Niles
Lockheed Martin Astronautics
P.O. Box 179
M/S SB071
Denver, CO 30201
303/977-3679

Mr. Stephen T. Noble
Rice University
P.O. Box 244
Tavernier, FL 33070
305/852-8879

Mr. Mauro Novara
ESA/ESTEC
Postbus 299
2200 AG Noordwijk, THE NETHERLANDS
31171984003

O -

Mr. Marvin L. Odefey
Lockheed Martin Astronautics
P.O. Box 179
Mail Stop S8110
Denver, CO 80201
303/977-7782

Mrs. Cinthya Ottonello
University of Genoa
Dipartimento di Ingegneria Biofisica
ed Elettronica
Via all' Opera Pia 11 A
16145, Genova, ITALY
39103532187

Dr. K.-I. Oyama
The Institute of Space and Astronautical
Science
3-1-1, Yoshinodai, Sagamihara, Kanagawa 229
Japan
0427513911

P -

Mr. L. Marco Palenzona
ESA/ESTEC
Postbus 299
2200 AG Noordwijk (zH),
THE NETHERLANDS
31171983651

Dr. Dennis Papadopoulos
University of Maryland
Dept. of Physics
College Park, MD 20742
301/405-1526

Dr. Monica Pasca
Universita di Roma "La Sapeinza"
Dipartimento di Ingegneria
Strutturale e Geotecnica
Via Eusossiana, 18-00184 Roma, ITALY
39644585156

Mr. Barry R. Payne
Bristol Aerospace Limited
600 Berry Street
Winnipeg, Manitoba, R3C 2S4 CANADA
204/775-8331

Mrs. Amey R. Peltzer
Naval Research Laboratory
Code 8123, Building 58 R127
4555 Overlook Avenue, S.W.
Washington, DC 20375
202/767-3982

Dr. Paul A. Penzo
Jet Propulsion Lab
1800 Oak Grove Drive
Pasadena, CA 91109
818/354-6162

Mrs. Maria Antonietta Perino
Alenia Spazio S.p.A.
Corso Marche, 41
10146 Torino, ITALY
39117180712

Mr. Paolo Piantella
Alenia Spazio S.p.A.
Corso Marche, 41
10146 Torino, ITALY
3911712923

Mr. Engelbert Plescher
FH Aachen, Space Department
Hohenstaufenallee 6
D-52064, Aachen, GERMANY
24160092394

Prof. J. David Powell
Stanford University
Aero/Astro Department
MC 4035
Stanford, CA 94305
415/723-3425

Prof. Jordi Puig-Suari
Arizona State University
Dept. of Mechanical
and Aerospace Engineering
Box 876106
Tempe, AZ 85287-6106
602/965-4363

R -

Prof. W. John Raitt
Utah State University
Dept. of Physics
CASS/UMC 4405
Logan, UT 84322
801/797-2849

Mr. Ray D. Rhew
NASA, Langley Research Center
M/S 238
Hampton, VA 23681
757/864-4705

Mr. Charles C. Rupp
NASA, Marshall Space Flight Center
Mail Code PS04
Huntsville, AL 35812
205/544-0627

S -

Mr. Dieter Sabath
Lehrstuhl für Raumfahrttechnik, TU
München, GERMANY
498921052176

Mr. Jean Sabbagh
Agenzia Spaziale Italiana
V.le Regina Margherita, 202
00198 Roma, ITALY

Ms. Salma I. Saeed
Stanford University
P.O. Box 14213
Stanford, CA 94309
415/725-3297

Prof. Juan R. Sanmartin
Escuela Técnica Superior de
Ingenieros Aeronáuticos
Universidad Politécnica de Madrid
Plaza Cardenal Cisneros, 3
28040 Madrid, SPAIN
3413366302

Mr. Andrew D. Santangelo
The Michigan Technic Corporation
17133 Inavale
Holland, MI 49424
616/399-4045

Dr. S. Sasaki
The Institute of Space and Astronautical
Science
3-1-1, Yoshinodai, Sagami-hara, Kanagawa 229
Japan
0427513911

Mr. Chikatoshi Satoh
Nihon University
College of Science and Technology
Dept. of Aerospace Engineering
7-24-1, Narashinodai, Funabashi-City,
274 JAPAN

Mr. Andreas Schroerer
Ruhr-Universität Bochum
Theoretische Physik IV
D-44780 Bochum, GERMANY
492347003729

Mr. John D. Schumacher
NASA Headquarters
Acting Associate Administrator
External Affairs
Washington, DC 20546

Mr. Thomas J. Settecerrri
Lockheed Martin Astronautics
2400 NASA Road 1 / C-104
Houston, TX 77058
713/483-4160

Prof. Irwin I. Shapiro
Harvard-Smithsonian Center
for Astrophysics
60 Garden Street
MS 45
Cambridge, MA 02138

Dr. Carl L. Siefring
Naval Research Laboratory
Plasma Physics Division
Code 6755
Washington, DC 20375
202/767-2467

Mr. Charles W. Shaw
NASA, Johnson Space Center
Flight Director Office
Mail Code DA8
Houston, TX 77058
713/483-5416

Mr. H. Frayne Smith
NASA, Marshall Space Flight Center
Mail Code EJ23
Huntsville, AL 35812
205/544-3572

Dr. Roberto Somma
Alenia Spazio S.p.A.
via Saccomuro, 24
00131 - Rome, ITALY
39641513208

Ms. Becky C. Soutullo
NASA, Marshall Space Flight Center
TSS Project Office
MSFC/JA71
Marshall Space Flight Center, AL 35812
205/544-1977

Mr. David Spencer
Naval Research Laboratory
Code 8213
4555 Overlook Avenue, S.W.
Washington, DC 20375-5000
202/767-6425

Dr. Curtis H. Spenny
U.S. Air Force Institute of Technology
AFIT/ENY
2950 P Street
Building 140
Wright-Patterson AFB, OH 45433-7765
513/753-6565

Mr. John H. Stadler
NASA, Langley Research Center
Mail Stop 431
Hampton, VA 23681-0001
757/864-7076

Dr. Wolfgang Steiner
Technical University of Vienna
Institute of Mechanics
Wiedner Hauptstrasse 8-10/325
A-1040 Vienna, AUSTRIA
431588015516

Dr. Nobie H. Stone
NASA, Marshall Space Flight Center
Space Physics Laboratory
Huntsville, AL 25812
205/544-7642

Ing. Bruno Strim
Alenia Spazio S.p.A. - Turin Plant
Scientific Satellites Directorate
Corso Marche, 41
10146 Torino, ITALY
39117180733

Mr. Locke M. Stuart
NASA, Goddard Space Flight Center
Code 920
Greenbelt, MD 20771
301/286-6481

Mr. Thomas D. Stuart
NASA Headquarters
Mail Code MO
Washington, DC 20560
202/358-4422

Mr. Francesco Svelto
ASI
Viale Regina Margherita 202
V.Le Rue Margerita, 202
00198 Rome, ITALY

T -

Prof. Giorglo Tacconi
Universita' di Genova
Dipartimento Ingegneria Biofisica
ed Elettronica
Via Opera Pia, 11 A
Genova, 16145, ITALY
39103532187

Dr. David L. Talent
Lockheed Martin Astronautics
2400 NASA Road 1
Mail Code C-104
Houston, TX 77058
713/483-5837

Mr. Zhaozhi Tan
Howard University
2300 6th Street, N.W.
Washington, DC 20059
202/806-4842

Dr. Patrick T. Taylor
NASA, Goddard Space Flight Center
Geodynamics
Code 921
Greenbelt, MD 20771
301/286-5412

Mr. Paul Tetzlaff
Daimler-Benz Aerospace / RST Rostock
Am Strom 109
D-18119 Warnemunde, GERMANY
4938156259

Ms. Shannon Thornburg
Stanford University
419 E. Indiana Street
Rapid City, SD 57701
605/394-2452

Mr. Donald D. Tomlin
NASA, Marshall Space Flight Center
Structures and Dynamics Lab
Mail Code ED13
Marshall Space Flight Center, AL 35812
205/544-1465

Mr. P. Chewning Toulmin
Hughes - STX
C/O Dr. W.J. Webster, Jr.
NASA, Goddard Space Flight Center
Code 920.2
Greenbelt, MD 20771
301/286-4506

Mr. Steven G. Tragesser
Purdue University
1282 Grissom Hall
West Lafayette, IN 47707-1282
317/494-5813

Prof. Hans Troger
Technical University of Vienna
Institute of Mechanics
Wiedner Hauptstrasse 8-10/325
A-1040 Vienna, AUSTRIA
431588015510

Mr. George Tyc
Bristol Aerospace Limited
660 Berry Street
P.O. Box 874
Winnipeg, Manitoba, R3C 2S4 CANADA
204/775-8331

U -

Dr. Maximilian Ullmann
Fiat
1776 Eye Street, N.W. #775
Washington, DC 20006
202/862-1614

V -

Prof. Sergio Vetrella
Dip. di Ingegneria Aerospaziale
Seconda Universita' di Napoli
Via Roma, 29
81031 Aversa (CE)
tel +39-81-5044035

Dr. Frank R. Vigneron
Canadian Space Agency
P.O. Box 11490
Station H
Ottawa, Ontario, K2H 82S CANADA
613/998-2741

Mr. Giuseppe Viriglio
Alenia Spazio S.p.A.
Corso Marche 41
10146 Torino, ITALY

W -

Mr. Bruce K. Wallace
NASA, Marshall Space Flight Center
EL64
Marshall Space Flight Center, AL 35812
205/544-1306

Dr. William J. Webster, Jr.
NASA, Goddard Space Flight Center
Code 920.0
Greenbelt, MD 20771
301/286-4506

Mr. Kenneth J. Welzyn
NASA, Marshall Space Flight Center
Flight Dynamics Branch
ED-13
Marshall Space Flight Center, AL 35812
205/544-1731

Mr. Scott L. Wetzel
Allied Signal Technical Services Corp.
NASA SLR
7515 Mission Drive
Lanham, MD 20706
301/805-3987

Prof. Paul J. Wilbur
Colorado State University
Dept. of Mechanical Engineering
60 Garden Street
Fort Collins, CO 80523
303/491-8564

Mr. John Williams
Hughes Research Laboratory
3011 Malibu Canyon Road
Malibu, CA 90265
310/317-5446

Mr. Scott Williams
Stanford University
STARIAB/ Durand 33 / 4055
Stanford, CA 94305
415/725-0482

Dr. Thomas L. Wilson
NASA, Johnson Space Center
Houston, TX 77058
713/483-2147

Mr. Dennis Ray Wingo
University of Alabama in Huntsville
Center for Space Plasama
and Aeronomic Research
Huntsville, AL 35899
205/895-6912

Dr. George L. Withbroe
NASA Headquarters
Code SS
Washington, DC 20546
202/358-1544

Dr. George M. Wood
101 Research Drive
Hampton, VA 23666-1340
757/865-1894

Mr. Alfred C. Wright
Lockheed Martin Astronautics
2550 E. Pine Bluff Lane
Highlands Ranch, CO 80210
303/977-5952

Mr. N. Convers Wyeth
Science Applications International Corp.
1710 Goodridge Drive
M/S 2-3-1
McLean, VA 22102
703/821-4411

Z -

Mr. Michael F. Zedd
Naval Research Laboratory
4555 Overlook Avenue, S.W.
Code 8233
Washington, DC 20375-5355
202/404-8337

Acknowledgments

This edition of the handbook is dedicated to the memory of the people involved in the advancement of tethers who are no longer with us, among them Stanley Shawan, Billy Nunley and Silvio Bergamaschi.